

Authorized Representative's

Business Name:

Planning/Zoning Application

Submitted On:

Mar 15, 2024, 05:19PM EDT

Planning & Zoning Department

Parcel Number: (Include ALL parcels)	WD-D0076
Nearest property address to the project site:	Street Address: O Venture Avenue City: DePere State: W Zip: 54115
Check each project type that is being applied for:	Site Plan
Current De Pere Zoning Districts:	I
Existing Site Land Uses:	Undeveloped/Vacant/Agricultural
Proposed Site Land Uses:	Business Park/Industrial
Does the project comply with the Comprehensive Plan?	Yes
Has City Staff been contacted for a pre-consultation meeting?	Yes
Property Owner:	First Name: City of DePere Last Name: Contract for Purchase by Massman Corp
Is the property owner's address the same as the nearest property address?	No
Property Owner's Address:	Street Address: N/A City: Menasha State: W Zip: 54952
Property Owner's Phone Number:	9208107790
Property Owner's Email Address:	jdavel@ new.rr.com
Is someone processing the project for the property owner as their authorized representative?	Yes
Authorized Representative's Name:	First Name: John Last Name: Davel
Anathanda al Daniero a cota tirra	

DAVEL ENGINEERING & ENVIRONMENTAL INC

Authorized Representate Phone Number:	tive's	920-560-6563
Authorized Representative's Email Address:		john@davel.pro
Please attach a PDF co site plan.	py of the	8047Planset 2024-03-14-signed.pdf
	you like a basic checklist mation to include in the n?	
How do you plan on paying for your application? Mail a check		Mail a check
Total Due:		\$350.00
Signature Data	Email Ad	ne: Davel dress: john@davel.pro John P Davel t: March 15, 2024 5:18pm America/New_York
User's Session Informat	tion	IP Address: 74.219.241.114

Referrer URL:

CITY OF DE PERE

335 South Broadway, De Pere, WI 54115 | www.de-pere.org



John Davel Davel Engineering & Environmental INC 1164 Province Terrace Menasha, WI 54952

RE: Site Plan Review for the New Massman Corporate INC at 2005 Venture AV

(Parcel WD-D0076)

Dear John:

Thank you for the revised site plan for the New Massman Corporate INC at 2005 Venture AV. The City of De Pere staff reviewed the site plan on May 10, 2024, and recommended approval, with the following condition that must be addressed prior to submitting a request for occupancy permits:

- Trees planted in the city terrace will need to be coordinated and marked by the City Forester. The City Forester will need to be on site when trees are planted to ensure correct procedures are followed. Contact the City Forester prior to installation to schedule dates/times to complete the tasks.
- After landscaping is installed, provide a statement from the landscaper that verifies that all landscaping has been installed according to the approved landscaping plan to minimize delays or violations related to this topic.
- After the exterior lighting is installed, provide a statement from the installer that the light spill from the property does not exceed the approved photometric plan.
- Provide updated plans that represent the final size and type of screening for the rooftop, wall, and ground mounted mechanical equipment and appurtenances. Provide confirmation that all are properly and completely screened per Zoning Ordinance 14-92(11).

You may now proceed to the Inspection Division to begin the process of obtaining permits. Should you have any questions regarding the decision or require further information, feel free to contact me at 339-4043 or pschleinz@deperewi.gov.

Sincerely,


Peter Schleinz

Senior Planner | Zoning Administrator

Futer Schlery

Daniel J. Lindstrom, AICP, Development Services Director cc:


Dennis Jensen, Senior Building Inspector



SCALE: 1" = 40'-0"

C1.0

CONSTRUCTION SERVICE DESIGN. BUILD. FINANCE.



— 799— Intermediate Contour - Existing

4/9/2024 10:49 AM J:\Projects\8047onp\dwg\Civil 3D\8047Topo.dwg Printed by: jennifer


608.81 8" PVC

620.91 24"

SALES: DRAWN BY: Author ARCHT. NO.:

SCALE: 1" = 40'-0"

CONSTRUCTION SERVICE DESIGN. BUILD. FINANCE.





- 1. Existing utilities shown are indicated in accordance with available records and field measurements. The contractor shall be responsible for obtaining exact locations & elevations of all utilities, including sewer and water from the owners of the respective utilities. All utility owners shall be notified by the contractor 72 hours prior to
- excavation. Contact Digger's Hotline (1-800-242-8511) for exact utility locations. 2. The Contractor shall verify all staking and field layout against the plan and field conditions prior to constructing the work and immediately notify the Engineer of any
- discrepancies. 3. The contractor shall minimize the area disturbed by construction as the project is constructed. Disturbed areas shall be seeded as soon as final grade is established. Contractor shall replace topsoil and then seed, fertilize and mulch all lawn areas within
- 1 week of topsoil placement.
- 4. Contractor shall remove all excess materials from the site. Earthwork contractors shall verify topsoil depth.
- 5. All sediment and erosion control devices and methods shall be in accordance with the Wisconsin DNR Technical Standards.
- 6. The contractor shall make weekly inspections and inspections within 1 day of any rainfall exceeding 0.5 inches of the sediment and erosion control devices throughout construction. The contractor shall repair or maintain erosion control devices as necessary. The inspection reports shall be made available to the owner at the end of the construction or upon demand during construction.

7. Parking lot striping shall be 4" painted safety yellow.

SALES: DRAWN BY: Author SHEET: SMET NO.: C1.2 ARCHT. NO.: **DATE:** 03/14/2024 **SCALE**: 1" = 40'-0"

MASSMAN CORPORAT 2005 Venture A

DRAINAGE GRADING

5/7/2024 4:30 PM J:\Projects\8047onp\dwg\Civil 3D\8047Engr.dwg Printed by: john

Railroad Tracks Benchmark Guy Wire Asphalt Pavement +799.9 Ex Spot Elevation Culvert Concrete Pavement — 800 — Index Contour - Existing Gravel — 799— Intermediate Contour - Existing Proposed Storm Manhole Proposed Building ——— 608 ——— Proposed Contour Proposed Curb Inlet Proposed Asphalt Prop. Catch Basin / Yard Drain — - - — Proposed Swale Proposed Concrete Proposed Endwall Proposed Culvert Proposed Gravel Prop. Flowline Spot Elev. Proposed Rip Rap Prop. Drainage Direction Prop. Top of Walk Elev. FF=000.0 Prop. Finished Floor Elev. Existing Grade

Railroad Signal

Post / Guard Post

Deciduous Tree

2" Iron Pipe Found

Government Corner

O ¾" Rebar Found

Sanitary MH / Tank / Base

Storm Manhole

Hydrant

Light Pole / Signal

Utility Pole

Clean Out / Curb Stop / Pull Box

LEGEND

— OH — Overhead Utility Lines

—E——E—— Underground Electric

——G———G——— Underground Gas Line


—w——w—— Water Main (Pipe Size)

Treeline

— San — San Sanitary Sewer (Pipe Size)

—Sto ——Sto ——Storm Sewer (Pipe Size)

Utility Guy Wire



2) Overland Flow

Railroad Signal

Post / Guard Post

Asphalt Pavement

Concrete Pavement

ිදිලි Deciduous Tree

O ¾" Rebar Found

2" Iron Pipe Found

Government Corner

Benchmark

Gravel

Sanitary MH / Tank / Base

Proposed Storm Manhole

Proposed Inlet Protection

Type of Inlet Protection

Prop. Catch Basin / Yard Drain

Proposed Urban Type B Erosion Mat

Proposed Class I Type B Erosion Mat

Proposed Class III Type B Erosion Mat

Proposed Curb Inlet

Proposed Endwall

Proposed Rip Rap

Storm Manhole

Hydrant

Utility Pole

Light Pole / Signal

+799.9 Ex Spot Elevation

Utility Valve

Guy Wire

Clean Out / Curb Stop / Pull Box

LEGEND

— OH — Overhead Utility Lines

—E——E—— Underground Electric

— G Underground Gas Line

——w———— Water Main (Pipe Size)

Culvert

— 799— Intermediate Contour - Existing

Railroad Tracks

Treeline

—Sto ——Sto ——Storm Sewer (Pipe Size)

Utility Guy Wire

Sanitary Sewer (Pipe Size)

Proposed Storm Sewer

Proposed Swale

Proposed Culvert

Proposed Silt Fence

Prop. Drainage Direction

Proposed Tracking Pad

Proposed Ditch Check

Proposed Building

Proposed Asphalt

Proposed Concrete

Proposed Gravel

- a) Silt Fence Intended to provide a temporary barrier to the transportation of sediment offsite. Silt fence also reduces the velocity of sheet flow; thereby reducing the erosion potential of flowing water. Silt fencing is not to be used in areas of channelized flow and sediment deposits shall be removed when a 6 inch depth is reached. The silt fence shall be repaired or replaced as necessary to maintain a barrier. All Silt Fence shall be installed and maintained in accordance with DNR Technical Standard 1056. It will be placed
- at the following locations: i) along the southern boundary of the pavement removal after topsoil has been replaced, unless the topsoil is
- immediately seeded and mulched. ii) and at the toe of soil piles if the pile will remain in place for more than seven (7) days.
- b) Sediment Bale Barrier Intended to intercept and detain small amounts of sediment from construction operations to prevent sediment from leaving the site. Sediment Bale Barriers are not to be used in areas of channelized flow. All Sediment Bale Barriers shall be installed and maintained in accordance with DNR Technical Standard 1055. Sediment Bale Barriers may be used in place of silt fence around soil
- c) Mulching Intended to reduce the amount of erosion caused by raindrop impact, high overland and concentrated flow velocities and assist the establishment of both temporary and permanent vegetation. All Mulching shall be installed and maintained in accordance with DNR Technical Standard 1058. d) Seeding - Intended to provide a reduction of overland flow velocities and stabilize disturbed areas. Seeding will be used on all disturbed areas within seven days of the completion of the activity that will disturb the area. All seeding shall be in accordance with DNR Technical Standard 1059. Seed mixture 40 (per WisDOT Specifications, Section 630) shall be applied at 5 pounds per 1000 square feet for permanent seeding prior to September 15th. If required, temporary seeding shall consist of Oats, Rye, Winter Wheat,

and/or Annual Ryegrass applied at rates and during the season specified by the Technical Standard but no

Ditch Checks shall be installed and maintained in accordance with DNR Technical Standard 1062.

later than November 1st. Sod placement may occur at anytime sod is available and the sod and soil are not

3) Trapping Sediment in Channelized Flow a) Ditch Checks - Intended to settle suspended sediment in channelized flow by reducing the flow velocity. All

- Pad shall be installed and maintained in accordance with DNR Technical Standard 1057. A tracking pad will be constructed at points where trucks are leaving existing pavements.
- implemented with use of methods provided in DNR Technical Standard 1068. These methods include the use of polymers, seeding, and mulch. 8) Dewatering BMP - Intended to reduce the amount of sediment conveyed due to dewatering practices.

7) Dust Control - Intended to reduce surface to air transport of dust during construction. **Dust control shall be**

- Dewatering practices require compliance with DNR Technical Standard 1061. The use of geotextile bags is required to prevent sedimentation. The bags shall meet the requirements of Technical Standard 1061. Dewatering BMP - Intended to reduce the amount of sediment conveyed as a result of dewatering practices
- Dewatering practices require compliance with DNR Technical Standard 1061. a) If dewatering is required, the contractor will need to direct the discharge to a stable outlet. A treatment channel is required. The pump shall discharge into a Type 1 Sediment Bag. The bag shall discharge to the treatment channel. The treatment channel shall consist of the following:
- i) A flat bottom that is eight-feet wide Length not less than fifty-feet. Actual length required to be determined by onsite soil test.
- iii) Lined with a woven separation fabric covered by jute netting. iv) ERO-TEX Floc Logs shall be placed in the channel perpendicular to the direction of flow. Spacing to be
- b) Prior to dewatering, Scott Bordeau from ERO-TEX shall be contacted to perform the sediment testing. Scott will select the proper Floc Log and determine the necessary length of the treatment channel. Scott can be reached at (608) 712-3839.
- c) Upon completion of the dewatering operation, all materials must be disposed of properly. The jute netting can be buried on site. The separation fabric must be removed from the site. Disposal of all materials shall be in accordance with all state and local requirements.
- 9) Concrete Washout Redi-mix trucks may wash-out into the proposed pavement gravel base for the initial pours. Washout from final pours must be contained and carried offsite for proper disposal. No concrete, or runoff from concrete washout is allowed to enter the storm sewer system

- Note: The dates provided are approximate for proposed construction and subject to weather conditions and overall project schedule. Several work items as listed above may occur simultaneously with others.

Maintenance Plan

- The contractor is responsible for inspection and maintenance of sediment and erosion control measures until the project is completed. The inspections shall be made every seven days or within 24-hours of a rainfall event of 0.50-inch or greater. Any practices that are damaged or not working properly shall be repaired by the end of the day. Accumulated sediment shall be removed when it has reached a height of one-half the height of the structure. In addition, the following measures shall be taken:
- planned practices to maintain a vigorous, dense vegetated cover. Remove silt fence and temporary structures only after final stabilization and vegetative cover is
- 3. Avoid the use of fertilizers and pesticides in or adjacent to channels or ditches.

1. All seeded areas will be re-seeded and mulched as necessary according to the specifications in the

4. Construction and waste materials shall be properly disposed. Weekly inspection reports shall be maintained by the contractor. These reports shall document inspections and maintenance performed. The date and time of the inspections, the inspector's name, and the status of construction and any maintenance performed. Refer to Appendix C of the Erosion and Sediment Control

Plan (report) or visit http://dnr.wi.gov/runoff/stormwater/constrforms.htm for a template. Upon request, the

inspection reports shall be made available to the owner, the engineer, the City of De Pere, or the Wisconsin

Responsible Parties

Best Management Practices (BMPs) Construction and Maintenance:

The Owner's Contractor, yet to be determined. Inspection and Compliance Enforcement

Department of Natural Resources.

City of De Pere Wisconsin Department of Natural Resources

SION & IMENT


OSIO DIME $\mathbb{R} \square \mathbb{Q}$

DRAWN BY: SALES: Author SHEET: SMET NO.: ARCHT. NO.:

DATE: 03/14/2024

SM/ POI

SCALE: 1" = 40'-0"



613.49 R-2. 614.02 0.0050 0.00 15797 0.90 4.34 4.0 R-3. 614.43 614.02 102 0.0040 0.00 19982 7535 12349 1544 1.02 3.44 R-4. 614.68 0.0030 0.00 23412 4900 1088 1.68 2.42 614.43 15680 R-5. 334 0.75 0.75 616.18 614.68 300 0.0050 0.00 10002 6720

40572

1560

1560

3.48

5.54

3.48

5.54

	STOR	M SEWE	R STRUC	TURE SUMM	ARY	
Structure	Туре	Size	Cover	Final Grade Rim	Invert	Depth
R-1.	Endwall				613.00	
R-2.	MH (48)	48" ID	R-1710	624.30	613.49	
R-3.	MH (48) Inlet	48" ID	R-3448-C	623.10	614.02	9.08
R-4.	MH (48) Inlet	48" ID	R-3448-C	623.07	614.43	8.64
R-5.	MH (48) Inlet	48" ID	R-3448-C	623.39	614.68	8.71
R-6.	MH (48) Inlet	48" ID	R-3448-C	620.31	616.18	4.13
R-9.	MH (48)	48" ID	R-1710	623.81	614.61	9.20
R-10.	Endwall				613.00	
R-11.	Endwall				613.99	(

40572

87390

0.00

0.00

0.0040

0.0070

R-3.

R-4.

R-9.

R-2.

614.61

613.99

613.49

613.00

280

LEGEND

— OH — Overhead Utility Lines

— San — San — Sanitary Sewer (Pipe Size)

—Sto ——Sto ——Storm Sewer (Pipe Size)

——G———G——— Underground Gas Line

—w——w—— Water Main (Pipe Size)

— 800 — Index Contour - Existing

Culvert

Proposed Culvert

Proposed Building

Proposed Asphalt

Proposed Gravel

Proposed Concrete

— 799— Intermediate Contour - Existing

Treeline

Railroad Tracks

— – – — Proposed Swale

Utility Guy Wire

Sanitary MH / Tank / Base

Proposed Sanitary Manhole

Prop. Catch Basin / Yard Drain

Proposed Storm Manhole

Proposed Curb Inlet

Proposed Endwall

Proposed Hydrant

Proposed Valve

Proposed Curb Stop

Proposed Cleanout

DS Proposed Downspout

Storm Manhole

Hydrant

Utility Valve

Utility Pole

Light Pole / Signal

+799.9 Ex Spot Elevation

Guy Wire

Clean Out / Curb Stop / Pull Box

🕌 Railroad Signal

Post / Guard Post

Deciduous Tree

2" Iron Pipe Found

Government Corner

Asphalt Pavement

Concrete Pavement

Proposed Reducer

Proposed Water MH

Proposed Plug

Proposed Tee

Proposed Cross

Proposed 90° Bend

Proposed 45° Bend

Proposed 22.5° Bend

O ¾" Rebar Found

Benchmark

Gravel

Sign



3.6

The outside services are shown to stop at a point 5 feet outside the foundation wall. The Contractor shall be responsible for coordination of continuation of the services into the building to properly coincide with the interior plumbing plans, and compliance with all plumbing permits.

The Contractor is responsible for compliance with Department of Safety & Professional Services, Chapter SPS 382, for lateral construction and cleanout locations.

The contractor shall coordinate with provider for electric, gas, and telecommunication service connection and relocations.

Pipe lengths are measured to center of structure. Endwalls are included in pipe length. Water Pipe shall be PVC C900 D(18), with minimum of 18 gauge, insulated (blue), single-conductor copper tracer wire, or equivalent, per SPS 382.40 (8)(k).

Sanitary Sewer Pipe shall be PVC Schedule 40, with minimum of 18 gauge, insulated (green), single-conductor copper tracer wire, or equivalent, per SPS 382.30 (11)(h).

Storm Sewer Pipe shall be PVC SDR(35), Reinforced Concrete Class III, or HDPE, AASHTO M 294, Type S with water tight joints, with minimum of 18 gauge, insulated (brown), single-conductor copper tracer wire, or equivalent, per SPS 382.36 (7)(d)10.a.

Water services are to be pressure tested and safe sampled prior to turning the service valve to the

Low pressure air test the sanitary sewer laterals prior to final connection to the lateral stub to ensure there is no inflow or infiltration. Provide test results to the City of DePere Engineering Division. ARCHT. NO.: Endwall pipes shall be encased in rip-rap with erosion mat type HR.

The water meter size is anticipated to be 1 inch.


5/7/2024 4:34 PM J:\Projects\8047onp\dwg\Civil 3D\8047Engr.dwg Printed by: john

DATE: 03/14/2024 **SCALE**: 1" = 40'-0"

DRAWN BY:

SMET NO.:

Author



CONSTRUCTION SERVICE DESIGN. BUILD. FINANCE.

ONST


SALES:

DRAWN BY: Author SHEET: C2.

DATE: 03/14/2024

5/1/2024 1:44 PM J:\Projects\8047onp\dwg\Civil 3D\8047Engr.dwg Printed by: jennifer

SMET NO.: ARCHT. NO.:



1. Prepare soil before installing Rolled Erosion Control Products (RECP's), including any necessary application of lime, fertilizer,

Note: When using cell-o-seed do not seed prepared area. Cell-o-seed must be installed with paper side down. 2. Begin at the top of the channel by anchoring the RECP's in a 6" (15 cm) deep x 6" (15 cm) wide trench with approximately 12" (30 cm) of RECP's extended beyond the up-slope portion of the trench. Anchor the RECP's with a row of staples/stakes approximately 12" (30 cm) apart in the bottom of the trench. Backfill and compact the trench after stapling. Apply seed to compacted soil and fold remaining 12" (30 cm) portion of RECP's back over seed and compacted soil. Secure RECP's over

compacted soil with a row of staples/stakes spaced approximately 12" (30 cm) across the width of the RECP's. 3. Roll center RECP's in direction of water flow in bottom of channel. RECP's will unroll with appropriate side against the soil surface. All RECP's must be securely fastened to soil surface by placing staples/stakes in appropriate locations as shown in the staple pattern guide. When using the DOT system, staples/stakes should be placed through each of the colored dots corresponding to the appropriate staple pattern.


4. Place consecutive RECP's end over end (shingle style) with a 4" - 6" (10 cm - 15 cm) overlap. Use a double row of staples staggered 4" (10 cm) apart and 4" (10 cm) on center to secure RECP's.

5. Full length edge of RECP's at top of side slopes must be anchored with a row of staples/stakes approximately 12" (30 cm) apart in a 6" (15 cm) deep x 6" (15 cm) wide trench. Backfill and compact the trench after stapling. 6. Adjacent RECP's must be overlapped approximately 2" - 5" (5cm - 12.5 cm) (depending on RECP's type) and stapled.

7. In high flow channel applications a staple check slot is recommended at 30 to 40 foot (9 M - 12 M) intervals. Use a double row of staples staggered 4" (10 cm) apart and 4" (10 cm) on center over entire width of the channel. 8. The terminal end of the RECP's must be anchored with a row of staples.stakes approximately 12" (30 cm) apart in a 6" (15

* In loose soil conditions, the use of staple or stake lengths greater than 6" (15 cm) may be necessary to properly anchor the

9. Detail provided by North American Green (www.nagreen.com)



C. Channel Bottom/side slope vertices

cm) deep x 6" (15 cm) wide trench. Backfill and compact the trench after stapling.

A. Overlaps and seams B. Projected Water line

* Horizontal staple spacing should be altered if necessary to allow staples to secure the critical points along the channel surface.

** In loose soil conditions, the use of staple or stake lengths greater than 6" (15 cm) may be necessary to properly anchor the RECP's.

1. Prepare soil before installing Rolled Erosion Control Products (RECP's), including any necessary application of lime, fertilizer, and seed.

Note: When using cell-o-seed do not seed prepared area. Cell-o-seed must be installed with paper side down. 2. Begin at the top of the slope by anchoring the RECP's in a 6" (15 cm) deep x 6" (15 cm) wide trench with approximately 12" (30 cm) of RECP's extended beyond the up-slope portion of the trench. Anchor the RECP's with a row of staples/stakes approximately 12" (30 cm) apart in the bottom of the trench. Backfill and compact the trench after stapling. Apply seed to compacted soil and fold remaining 12" (30 cm) portion of RECP's back over seed and compacted soil. Secure RECP's over compacted soil with a row of staples/stakes spaced approximately 12" (30 cm) apart across the width of the RECP's. 3. Roll the RECP's (A.) down or (B.) horizontally across the slope. RECP's will unroll with appropriate side against the soil surface. All RECP's must be securely fastened to soil surface by placing staples/stakes in appropriate locations as shown in the staple pattern guide. When using the Dot system, staples/stakes should be placed through each of the colored Dots corresponding to the appropriate staple pattern.

4. The edges of parallel RECP's must be stapled with approximately 2" - 5" (5 cm - 12.5 cm) overlap depending on RECP's type. 5. Consecutive RECP's spliced down the slope must be placed end over end (shingle style) with an approximate 3" (7.5 cm) overlap. Staple through overlapped area, approximately 12" (30 cm) apart across entire RECP's width. Note: * In loose soil conditions, the use of staple or stake lengths greater than 6" (30 cm) may be necessary to properly secure

6. Detail provided by North American Green (www.nagreen.com) 7. Turf Reinforcement Mats (TRM's) shall be installed in accordance with the above specifications for all RECP's. Anchoring size and pattern is to be installed per manufacturer specifications for clay soils having 4:1 slope. All TRM's shall be topsoil filled,

seeded, and covered with a Class 2, Type B erosion mat in accordance with all manufacturer specifications.

GENERAL NOTES:

Product Acceptability list may be substituted.

block the entire height of the curb box opening.

Inlet protection devices shall be maintained or replaced at the direction of the

Manufactured alternatives approved and listed on the DOT Erosion Control

When removing or maintaining inlet protection, care shall be taken so that the

See Note 1

See Note 2

sediment trapped on the geotextile fabric does not fall into the inlet. Any


. Finished size, including flap pockets where required, shall extend a minimum of 10" around the perimeter to facilitate maintenance or removal.


material falling into the inlet shall be removed immediately.


3. Flap pockets shall be large enough to accept wood 2x4.


EROSION/TURF REINFORCEMENT MAT SLOPE INSTALLATION

DNR TECHNICAL STANDARD 1052









1. Excavate below channel outlet and widen channel outlet to the required riprap thickness for each apron. Foundation to be set to zero grade and 2. Place geotextile fabric on bottom and sides of prepared foundation.

Fabric shall extend under endwall in accordance with DOT specifications. (DOT Section 628.2 & 628.3) 3. Exercise care in placement of riprap to avoid damage to filter fabric. 4. Use riprap conforming to Wisconsin DOT specifications. (DOT Section


5. Use DOT Type R geotextile fabric for light riprap. Use Type HR for medium and heavy riprap. (DOT Section 606.2, 606.3, 628.2 & 628.3) 6. Use 12" dimension for pipes less than 12" in diameter.


OUTLET PROTECTION


Inlet Specifications

Dimension Length and Width to Match

as Per the Plan








Stake installation shall meet manufacturer's requirements in regard to spacing, material, size, and bury depth. SEDIMENT LOG DETAIL

EROSION MAT CHANNEL INSTALLATION

DNR TECHNICAL STANDARD 1053



TRACKING PAD DETAIL DNR TECHNICAL STANDARD 1057

Note 1 Use hard, durable, angular stone or recycled concrete meeting the gradation in Table 1. Where this gradation is not available, meet the gradation in Wisconsin Department of Transportation (DOT) 2022 Standard Specification, Section 312, Select Crushed Material.

Note 2 Slope the stone tracking pad in a manner to direct runoff to an approved treatment practice.


Note 3 Select fabric type based on soil conditions and vehicles loading.

Note 4 Install tracking pad across full width of the access point, or restrict existing traffic to a dedicated egress lane at least 12 feet wide across the

Note 5 If a 50' pad length is not possible due to site geometry, install the maximum length practicable and supplement with additional practices as


TABLE 1: GRADATION FOR STONE TRACKING PADS Percent by weight passing

2-1/2" 90-100 1-1/2" 25-60 3/4" 0-20



Type FF (DOT Section 328.2 & 628.3) Shall Extend

INLET PROTECTION, TYPE A



INLET PROTECTION, TYPE B

(CAN BE INSTALLED IN ANY INLET WITHOUT A CURB BOX)

INSTALLATION NOTES: Inlet protection Type A shall be utilized around field inlets until permanent stabilization methods have been established. Inlet protection Type A shall be utilized on pavement inlets prior to installation of curb and gutter or pavement.

The contractor shall demonstrate a method of maintenance, using a sewn flap,

hand holds, or other method to prevent accumulated sediment from entering

once surrounding surface is in place. Inlet protection Type C shall be utilized on street inlets with curb heads.

Inlet protection Type B shall be utilized on street inlets without curb heads,

TYPE B & C Trim excess fabric in the flow line to within 3" of the grate.


2. For inlet protection, Type C (with curb box), an additional 10" of fabric is wrapped around the wood and secured with staples. The wood shall not For Inlets With Cast Curb Box Use Wood 2"x4", Extend 10" Beyond Grate Width on Both Front, Back and Bottom to be Made From Single Piece of Fabric 4"x6" Oval Hole Shall be Heat Cut Into All Four Side Panels Stitched Seams All Around Side Pieces and on Flap Pockets Wood 2" x 4" Extends 8" Beyond Grate Width on Both Sides, Length Varies. Secure to Grate With Wire or Plastic Ties INLET PROTECTION, TYPE C

INLET PROTECTION, TYPE D

(CAN BE INSTALLED IN ANY INLET WITH OR WITHOUT A CURB BOX) **INSTALLATION NOTES:** Do not install inlet protection type D in inlets shallower than 30", measured from

the bottom of the inlet to the top of the grate. Trim excess fabric in the flow line to within 3" of the grate.

The installed bag shall have a minimum side clearance between the inlet walls and the bag measured at the bottom of the overflow holes of 3". Where necessary, the contractor shall cinch the bag using plastic zip ties to achieve the 3" clearance. The ties shall be placed at a minimum of 4" from the bottom of the



1. Detail of construction not shown on this drawings shall conform to criteria set by authorities having

jurisdiction and by DNR Technical Standard 1056.

2. When possible, the silt fence should be constructed in an arc or horseshoe shape with the ends pointing upslope to maximize both strength and effectiveness. 3. Attach the fabric to the posts with wire staples or wooden lath and nails.

4. 8'-0" post spacing allowed if a woven geotextile fabric is used. 5. Trench shall be a minimum of 4" wide and 6" deep to bury and anchor the geotextile fabric. Fold material to fit trench and backfill and compact trench with excavated soil.

6. Geotextile fabric shall be reinforced with an industrial polypropylene netting with a maximum mesh spacing of 3/4" or equal. A heavy-duty nylon top support chord or equivalent is required. 7. Steel posts shall be studded "tee" or "u" type with a minimum weight of 128 lbs/lineal foot (without anchor). Fin anchors shall be a minimum size of 4" diameter or 1 1/2" x 3 1/2", except wood posts

SILT FENCE INSTALLATION

DNR TECHNICAL STANDARD 1056

for geotextile fabric reinforced with netting shall be a minimum size of 1 1/8" x 1 1/8" oak or

CONSTRUCTION S DESIGN. BUILD. F

SALES:


DRAWN BY: Author SMET NO.:

ARCHT. NO.:

DATE: 03/14/2024

4/18/2024 9:56 AM J:\Projects\8047onp\dwg\Civil 3D\8047Engr.dwg Printed by: jennifer

C2.2



SALES:

Author

DATE: 03/14/2024

SCALE: 1" = 40'-0"

1 + 0.0 + 0.0, + 0.0 + 0.0, + 0.0 + 0.0, + 0 ** to 0. 1 a column 1 $\frac{1}{4}$ $- 4 \\ - 5$ $\overline{0}$ 0.0 1 $t_{0.0}$ $t_{0.$ 0.0 1/ $t_{0.0} = t_{0.0} = t_{0.$ $\frac{1}{0}$ ***Opt ** Told 0.0 †
0.0 † 1 0.0 1 0 1 1 2 1 2 1 1 1 1 1 0 1 0 0 0 0 0 1 0 3 1 0 2 1 0 1 1 0 1 1 0 0 1 0 10 + 24 + 27 + 28 + 2.5 + 1.5 .4⁺\$-\$⁺\$
[4⁺⁶·7⁺0·1^{+} \$\$\$\frac{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frac{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_8}{\pi_8}\frace{\pi_ 4.9 1/2.8 19.1/2.1/15.5 13.9 1/2.7 1/1.8 1/1.2 1/0.8 1/1.2 1/0.8 1/0.5 1/0.2 1/0.7 4.9 */ 6 * 8 * 4 */ 1 * 5.3 * 3.8 * 2.6 * 1.8 * 1.2 * 6.7 * 1.6 * 1.2 * 6.7 * 1.6 * 1.7 6.7 * 6.7 * 6.7 * 6.0 * **36** 4.5 5.3 45.0 45.9 42.0 42.1 4.5 14.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 40/1 4.0 5/1.0 5/1 4.0 5/1
2.7⁺3.4⁺3.8⁺3.8⁺3.8⁺3.8⁺3.8⁺3.8⁺3.8⁺3.6⁺0.4^{*}0.2^{*}0.4^{*}0.2^{*}0.4^{*}0.2^{*}0.0[†]0.0^{*}0.0[†]0.0^{†} + 0.0 :0⁺2.4⁺2.7⁺2.6⁺2.4⁺1.9⁺1.4⁺1.0⁺1.0⁺1.0,8⁺0.5⁺1.0,9⁺0.2⁺0.1⁺0.9⁺0.0 \$\frac{1}{2} \frac{1}{2} \frac **1.6 ⁺0.8 ⁺0.8 ⁺0.9 ⁺0.9 ⁺0.9 ⁺0.4 ⁺0.8 ⁺0.4 ⁺0.4 ⁺0.4 ⁺0.8 ⁺0.4 ⁺0.7 5, 2 ⁺0.1 ⁺0.7 5, 2 ⁺0.1 ⁺0.9 ⁺0.0 ^{**} **67** to \$1,9 1,0 1,9 1,0 1,9 1,0 1 1,0 1 1,0 1 1,0 1 1,0 1,0 1,0 1,0 1,0 1,0 1 #\$\frac{1}{1}\frac{1}{2}\frac{1}{3}\frac{1}{12}\frac{1}{3}\frac{1}{12}\frac{1}{3}\frac{1}{12}\frac{1}{3}\frac{1}{12}\frac{1}{12}\frac{1}{13}\frac{1}{12}\frac{1}{12}\frac{1}{13}\frac{1}{12}\frac{1}{12}\frac{1}{13}\frac{1}{12}\frac{1}{12}\frac{1}{13}\frac{1}{12}\frac{1}{1 \$\frac{\frac
\$\frac{4.5\frac{5}{6.1}\frac{4.8\frac{7}{3.7\frac{7}{2.7\frac{7}{2.0\frac{7}{4.0\frac{7}{0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.0 + 0.1 + 0.1 + 0.2 + 0.3 + 0.3 + 0.4 + 0.5 + 0.6 + 0.6 + 0.6 + 0.6 + 0.5 + 0.6 + 0.5 \$\frac{1}{2}\frac{1}{5}\frac{4}{6}\frac{5}{5}\frac{4}{4}\frac{4}{3}\frac{7}{2}\frac{7}{3}\frac{1}{6}\frac{7}{1}\frac{7}{3}\frac{7}{6}\frac{7}{5}\frac{1}{2}\frac{7}{3}\frac{7}{1}\frac{7}{3}\frac{7}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac{7}{3}\frac + 0.0 + 0.1 + 0.1 + 0.2 + 0.2 + 0.2 + 0.3 + 0.3 + 0.3 + 0.3 + 0.3 + 0.3 + 0.3 + 0.2 5.9 [†]8.8 [†]8.6 [†]6.6 [†]4.9 [†]3.4 [†]2.4 [†]1.6 [†]1.0 [†]0.6 [†]0.9 [†]0.2 [†]0.1 [†]0.0 [†]0 5.0 ⁺8.7 ⁺8.4 ⁺6.6 ⁺4.8 ⁺3.4 ⁺2.3 ⁺1.5 [†]1.0 ⁺0.6 ⁺0.4 [†]0.2 ⁺0.1 [†]0.0 [†]0.6 [†]0.4 [†]0.2 [†]0.0 [†]0. $\frac{1}{4.8}$ $\frac{1}{6.6}$ $\frac{1}{6}$ $\frac{1}{7.2}$ $\frac{1}{5.9}$ $\frac{1}{4.4}$ $\frac{1}{3.1}$ $\frac{1}{2.2}$ $\frac{1}{1.5}$ $\frac{1}{1.0}$ $\frac{1}$ $\frac{1}{1.0}$ $\frac{1}{1.0}$ $\frac{1}{1.0}$ $\frac{1}{1.0}$ $\frac{1}{1.0}$ $^{+}4.1$ $^{+}5.3$ $^{+}5.7$ $^{+}5.0$ $^{+}3.7$ $^{+}2.7$ $^{+}1.9$ $^{+}1.3$ $^{+}0.9$ $^{+}0.6$ $^{+}0/3$ $^{+}0.2$ $^{+}0.1$ $^{+}0.0$
$^{+}0.0$ $^{+}$ $^{+}$ 3.2 $^{+}$ 3.9 $^{+}$ 4.2 $^{+}$ 3.9 $^{+}$ 3.0 $^{+}$ 2.2 $^{+}$ 1.6 $^{+}$ 1/2 $^{+}$ 0.8 $^{+}$ 0.5 $^{+}$ 0.3 $^{+}$ 0.1 $^{+}$ 0.1 $^{+}$ 0.0 $^{+}$ 0\$\\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\\ 0\$\\ 0\$\\\ 0 1.2 + 0.4 + 0.5 + 1.0
+ 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 1.0 + 8 7 9 9 7 9 \$\frac{\purple}{\purp 26 + 2.3 + 2.9 + 2.6 + 2.3 + 2.9 + 2.6 + 2.3 + 2.9 + 2.0 + 2 $\frac{1}{\sqrt{1}}$ \$\frac{1}{2}{5}{6}{5}{5}{7}{6}{5}{5}{5}{7}{6}{5}{5}{7}{5}{6}{7}{5}{5}{7}{5}{6}{7}{5}{5}{7}{5} $\frac{1}{1}$
\$\frac{\fractor}{\fractar} $\frac{1}{\sqrt{0}}$ $\frac{1}{\sqrt{5}}$ $\frac{1}{0}$ 0.0.0.1.0.0. $t_{0.0} + t_{0.0} + t_{0.$ $t_{0.0} + t_{0.0} + t_{0.$ CSM 8697 INV=613.50'

1. All outdoor lighting complies with zoning ordinance 15-95 for light trespass, dark sky compliance, light colors, and fixture

WPX0 LED ALO SWW2 WPX0 LED, 850-1,650 Adjustable Lumen Output (1,650 Default), Switchable CCT WPX2 LED 30K Mvolt WPX2 LED wallpack 6000lm 3000K color J1 ESX LED Area Luminaire Size 1 P2 Lumen ackage 3000K CCT Type R3 Distribution J2 Max: 7840cd Package 3000K CCT Type R3 Distribution with House-side shield


04/18/2024 Scale Not to Scale Drawing No. Summary

PROJECT FOR:

MASSMAN CORPORATE INC.

(AS SUCCESSOR BY MERGER TO EDL MASSMAN, LLC)

DEPERE, WISCONSIN



	_	LATEST SHEET REVISION			
NUMBER	SHEET NAME / DESCRIPTION	DATE	ISSUED BY	NUMBER	
1 TITLE					
T1.0	TITLE SHEET	04.29.24	LJP	D	
		-			
2 GENERAL					
G1.0	PLAN NOTES				
G1.1	PLAN NOTES				
G1.2	CODE DATA				
G1.3	CODE DATA				
3 CIVIL					
C1.0	SITE PLAN				
C1.1	TOPOGRAPHIC SURVEY				
C1.2	DRAINAGE & GRADING PLAN				
C1.3	EROSION & SEDIMENT CONTROL PLAN				
C1.4	UTILITY PLAN				
C2.1	CONSTRUCTION DETAILS				
C2.2	SEWER & WATER DETAILS				
C2.3	EROSION & SEDIMENT CONTROL DETAILS				
4 ARCHITECTUI	RAI				
A0.1	WALL / ROOF TYPES	04.29.24	LJP	D	
A1.0	FLOOR PLAN - PROPOSED				
A1.1	FLOOR PLAN - ENLARGED PLANS				
A1.2	FLOOR PLAN - OFFICE AREA DIMENSION PLAN				
A1.3	ROOF PLAN - PROPOSED	04.29.24	LJP	D	
A2.0	ELEVATION - EXTERIOR	04.29.24	LJP	D	
A3.0	SECTIONS - BUILDING				
A3.1	SECTIONS - BUILDING	04.29.24	LJP	D	
A3.2	SECTIONS - BUILDING	04.10.24	LJP	В	
A6.0	SCHEDULES - DOOR / WINDOW				
A6.1	ROOM FINISH PLAN - OVERALL				
A6.2	ROOM FINISH PLAN - OFFICE AREA	03.14.24	LJP	Α	
A6.3	REFLECTED CEILING PLAN - PROPOSED				
C CTDUCTUDAL					
5 STRUCTURAL					
S0.1	STRUCTURAL DESIGN CRITERIA	04.30.34	LID		
S1.0	FOUNDATION PLAN - OVERALL	04.29.24	LJP	D	
S1.1	SLAB PLAN - OVERALL				
S1.2	ANCHOR BOLT PLAN				
S1.3	ANCHOR BOLT DETAILS				

LJP

04.29.24

S2.0 FOUNDATION SCHEDULES & DETAILS

S3.0 FRAMING PLANS - VESTIBULE / SHOP REST.

S4.0 STRUCT. METAL STUD SCHEDULES & DETAILS

FRAMING PLAN - STANDALONE MEZZANINE

S2.1 FOUNDATION DETAILS S2.2 FOUNDATION DETAILS


SHEET INDEX





ARCHT. NO.:

DATE: 4/30/2024 7:52:12 AM

SCALE:









SMET CONSTRUCTION SERVICE CORP. DESIGN. BUILD. FINANCE.


SALES: SHEET: G1.1

SCALE: 3/8" = 1'-0"





OCCUPANCY CLASSIFICATION F-2, LOW-HAZARD FACTORY INDUSTRIAL B, BUSINESS



EGRESS PATH SCHEDULE				
MARK	TRAVEL DISTANCE	CLEAR WIDTH	COMMENTS	
FIRST FLOOR - EGRESS PATH 1	49'			
FIRST FLOOR - EGRESS PATH 2	90'			
FIRST FLOOR - EGRESS PATH 3	63'			
FIRST FLOOR - EGRESS PATH 4	70'			
FIRST FLOOR - EGRESS PATH 5	77'			
FIRST FLOOR - EGRESS PATH 6	170'			
FIRST FLOOR - EGRESS PATH 7	233'			
FIRST FLOOR - EGRESS PATH 8	208'			
FIRST FLOOR - EGRESS PATH 9	94'			
FIRST FLOOR - EGRESS PATH 10	159'			
FIRST FLOOR - EGRESS PATH 11	78'			
FIRST FLOOR - EGRESS PATH 12	91'			
FIRST FLOOR - EGRESS PATH 13	88'			
FIRST FLOOR - EGRESS PATH 14	103'			
FIRST FLOOR - EGRESS PATH 15	73'			

	FIRST FLOOR OCCUPANCY B					
ROOM						
NUMBER	ROOM NAME	AREA	FUNCTION OF SPACE	OCC. FACTOR	CAPACITY	
100	VESTIBULE	95 SF	CIRCULATION	0 SF		
101	RECEPTION	220 SF	BUSINESS	100 SF	2	
102	CONFERENCE	178 SF	TABLES AND CHAIRS	15 SF	12	
105	CORRIDOR	430 SF	CIRCULATION	0 SF		
106	STORAGE	Not Placed	ACCESSORY STORAGE	300 SF		
107	STORAGE	59 SF	ACCESSORY STORAGE	300 SF	0	
108	CONFERENCE	321 SF	TABLES AND CHAIRS	15 SF	21	
109	CUBICLE AREA	1540 SF	BUSINESS	100 SF	15	
110	OFFICE	95 SF	BUSINESS	100 SF	1	
111	OFFICE	95 SF	BUSINESS	100 SF	1	
112	OFFICE	180 SF	BUSINESS	100 SF	2	
113	OFFICE	118 SF	BUSINESS	100 SF	1	
114	OFFICE	118 SF	BUSINESS	100 SF	1	
115	OFFICE	118 SF	BUSINESS	100 SF	1	
116	OFFICE	118 SF	BUSINESS	100 SF	1	
117	OFFICE	118 SF	BUSINESS	100 SF	1	
118	JANITORS	53 SF	ACCESSORY STORAGE	300 SF	0	
119	RESTROOM	74 SF	RESTROOM	0 SF		
120	WOMENS	197 SF	RESTROOM	0 SF		
121	MENS	197 SF	RESTROOM	0 SF		
122	CUBICLE	1264 SF	BUSINESS	100 SF	13	
123	OFFICE	122 SF	BUSINESS	100 SF	1	
124	OFFICE	113 SF	BUSINESS	100 SF	1	
125	OFFICE	113 SF	BUSINESS	100 SF	1	
126	OFFICE	113 SF	BUSINESS	100 SF	1	
127	OFFICE	113 SF	BUSINESS	100 SF	1	
128	LOCKER ROOM	Not Placed	LOCKER ROOM	50 SF		
128	BREAKROOM	2119 SF	TABLES AND CHAIRS	15 SF	141	
130	PANTRY	Not Placed	ACCESSORY STORAGE	300 SF		
		8278 SF			220	

GENERAL CODE DATA EDL MASSMAN - DE PERE, WI SCOPE OF WORK: NEW CONSTRUCTION BUILDING USE: MANUFACTURING **BUILDING CODE** 2015 INTERNATIONAL BUILDING CODE **BUILDING AREA:** FIRST FLOOR OCCUPANCY F-2 AREAS 36,103 SQ FT OCCUPANCY B AREAS 8,792 SQ FT OCCUPANCY S-2 AREAS 660 SQ FT TOTAL BUILDING AREA: 45,555 SQ FT

OCCUPANCY GROUP: F-2, LOW HAZARD FACTORY INDUSTRIAL

OCCUPANCY F-2 TABLE 506.2 = 92,000 SQ FT

<u>ACTUAL</u>

36.5 FT

<u>ALLOWED</u>

75 FT

OCCUPANCY GROUP: S-2, LOW HAZARD STORAGE

506.3.3 AMOUNT INCREASE:

If = [F/P - 0.25]W/30PERIMETER: 880 FT FRONTAGE: 880 FT WIDTH: 30 FT

OCCUPANCY GROUP: B, BUSINESS

ALLOWABLE BUILDING HEIGHT:

ALLOWABLE STORIES: ALLOWABLE AREA:

E	EGRESS PATH SCHEDULE					
MARK	TRAVEL DISTANCE	CLEAR WIDTH	COMMENTS			
RST FLOOR - GRESS PATH 1	49'					
RST FLOOR - GRESS PATH 2	90'					
RST FLOOR - GRESS PATH 3	63'					
RST FLOOR - GRESS PATH 4	70'					
RST FLOOR - GRESS PATH 5	77'					
RST FLOOR - GRESS PATH 6	170'					
RST FLOOR - GRESS PATH 7	233'					
RST FLOOR - GRESS PATH 8	208'					
RST FLOOR - GRESS PATH 9	94'					
RST FLOOR - RESS PATH 10	159'					
RST FLOOR - RESS PATH 11	78'					
RST FLOOR - RESS PATH 12	91'					
RST FLOOR - RESS PATH 13	88'					
RST FLOOR - RESS PATH 14	103'					
RST FLOOR - RESS PATH 15	73'					

	Aa = [At + (NS x If)] Aa = [92,000 + (23,000 x 0.75)] =	= 109,250 SQ FT	
	(25,000 (25,000) 0 1 2 1	<u>ACTUAL</u>	ALLOWED 109,250 SQ FT
ALL	OWABLE AREA DETERMINED BY IBC	508.3 NONSEPAR	RATED OCCUPAN
CHAPTER 6	NSTRUCTION TYPE: IIB		
TAE	BLE 601:		
	BUILDING ELEMENTS PRIMARY STRUCTURAL FRAME	MIN H	OURS 0
	BEARING WALLS		U
	EXTERIOR		0
	INTERIOR		0
	NONBEARING WALLS AND PART EXTERIOR	TITIONS	0
	INTERIOR		0
	FLOOR CONSTRUCTION		0
	ROOF CONSTRUCTION		0
CHAPTER 9 BUI	LDING IS PROTECTED BY AN AUTOMA	ATIC FIRE SPRINK	LER PER NFPA 13
CHAPTER 10			
OC	CUPANT LOAD FIRST FLOOR OCCUPANCY B: 19	4 OCC	
	FIRST FLOOR OCCUPANCY F-2: 7		
	MEZZANINE S-2: 3 OCC		
	TOTAL OCCUPANT LOAD: 268 O	CC	
EXI	T ACCESS:		F-2, S-
	TABLE 1006.2.1 COMMON PATH TABLE 10017.2 EXIT ACCESS TRA		
CHAPTER 29	9		
PLU	IMBING FIXTURES REQUIRED		
	OCCUPANCY B		
	104 / 2 OZ NAENI AND OZ WONA	1 T N I	
	194 / 2 = 97 MEN AND 97 WOM 97 / 1 PER 25 FIRST 50 THEN 1 F		TER CLOSETS FOI
	194 / 2 = 97 MEN AND 97 WOM 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F	PER 50 = 2.94 WA	
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FO	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN 6 FOR MEN 6 FOR WOMEN R MEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN R WOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN R WOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN R WOMEN JNTAINS	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN R WOMEN JNTAINS	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 6.21 LAV PER 80 = 2.21	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN WOMEN WOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN WOMEN WOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUR TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUR TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR W 3.32 (4) WATER CLOSETS FOR W	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV INTAINS EN S FOR MEN S FOR WOMEN R MEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M 3.32 (4) WATER CLOSETS FOR MEN 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR MOM	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R MEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOMEN	TER CLOSETS FOI ATORIES FOR ME
	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 36 / 100 = 0.36 LAVATORIES FOU 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOU TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR W 3.32 (4) WATER CLOSETS FOR MEN 2.59 (3) LAVATORIES FOR MEN	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R MEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOMEN	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M 3.32 (4) WATER CLOSETS FOR M 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR MOM 2.05 (3) DRINKING FOUNTAINS	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUR TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M 3.32 (4) WATER CLOSETS FOR M 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR WOME 2.05 (3) DRINKING FOUNTAINS JMBING FIXTURE PROVIDED (5) WATER CLOSETS FOR WOME	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M 3.32 (4) WATER CLOSETS FOR M 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR MOM 2.05 (3) DRINKING FOUNTAINS	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR M 3.32 (4) WATER CLOSETS FOR M 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR WOME 2.05 (3) DRINKING FOUNTAINS JMBING FIXTURE PROVIDED (5) WATER CLOSETS FOR WOMEN (4) WATER CLOSETS FOR MEN (3) LAVATORIES FOR WOMEN (4) WATER CLOSETS FOR MEN (3) LAVATORIES FOR MEN (3) LAVATORIES FOR MEN	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUR TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR W 3.32 (4) WATER CLOSETS FOR W 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR WOME 2.05 (3) DRINKING FOUNTAINS JMBING FIXTURE PROVIDED (5) WATER CLOSETS FOR WOMEN (4) WATER CLOSETS FOR MEN (3) LAVATORIES FOR MEN (3) LAVATORIES FOR MEN (4) WATER CLOSETS FOR MEN (5) WATER CLOSETS FOR MEN (6) WATER CLOSETS FOR MEN (7) UNISEX WATER CLOSET	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JNTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED MEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME
PLU	97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 25 FIRST 50 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 97 / 1 PER 40 FIRST 80 THEN 1 P 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUI TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR W 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR WOME 2.59 (3) LAVATORIES FOR WOME 3.05 (3) DRINKING FOUNTAINS JMBING FIXTURE PROVIDED (5) WATER CLOSETS FOR WOMEN (4) WATER CLOSETS FOR WOMEN (3) LAVATORIES FOR WOMEN (4) WATER CLOSETS FOR MEN (3) LAVATORIES FOR MEN (3) LAVATORIES FOR MEN (4) WATER CLOSETS FOR MEN (5) WATER CLOSETS FOR MEN (6) UNISEX WATER CLOSET (1) UNISEX WATER CLOSET (1) UNISEX LAVATORIES	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JINTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED JEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME ATORIES FOR WO
PLU	97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 25 FIRST 50 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 97 / 1 PER 40 FIRST 80 THEN 1 F 197 / 100 = 1.97 DRINKING FOU OCCUPANCY F-2 71 / 2 = 36 MEN AND 36 WOME 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 WATER CLOSETS 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 36 / 100 = 0.36 LAVATORIES FOR 71 / 1,000 = 0.07 DRINKING FOU OCCUPANCY S-2 3 / 2 = 2 MEN AND 2 WOMEN 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 WATER CLOSETS 2 / 100 = 0.02 LAVATORIES FOR 3 / 1,000 = 0.01 DRINKING FOUR TOTAL PLUMBING FIXTURES REG 3.32 (4) WATER CLOSETS FOR W 3.32 (4) WATER CLOSETS FOR W 2.59 (3) LAVATORIES FOR MEN 2.59 (3) LAVATORIES FOR WOME 2.05 (3) DRINKING FOUNTAINS JMBING FIXTURE PROVIDED (5) WATER CLOSETS FOR WOMEN (4) WATER CLOSETS FOR MEN (3) LAVATORIES FOR MEN (3) LAVATORIES FOR MEN (4) WATER CLOSETS FOR MEN (5) WATER CLOSETS FOR MEN (6) WATER CLOSETS FOR MEN (7) UNISEX WATER CLOSET	PER 50 = 2.94 WA PER 50 = 2.94 WA PER 50 = 2.94 WA PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = 2.21 LAV PER 80 = MOMEN S FOR MEN S FOR WOMEN R WOMEN JINTAINS FOR MEN FOR WOMEN MEN WOMEN NTAINS QUIRED JEN JOMEN JOM	TER CLOSETS FOI ATORIES FOR ME ATORIES FOR WO





MASSMAN CORPORATE INC

SALES: DRAWN BY: Author SMET NO.: G1.2

DATE: 4/30/2024 7:52:14 AM

ARCHT. NO.:





CODE DATA PLAN KEY

ELEVATOR

3-HR FIRE BARRIER/WALL

OCCUPANCY CLASSIFICATION

INDUSTRIAL

FIRST FLOOR -

EGRESS PATH 15

FIRST FLOOR OCCUPANCY F-2

27549 SF WAREHOUSE

7718 SF WAREHOUSE

52 SF RESTROOM

52 SF RESTROOM

35370 SF

73'

FUNCTION OF SPACE OCC. FACTOR CAPACITY

500 SF

500 SF

0 SF


0 SF

F-2, LOW-HAZARD FACTORY

FIRE EXTINGUISHER


1-HR FIRE BARRIER/WALL

2-HR FIRE BARRIER/WALL



	N S	
KOJECI INFO:	MASSMAN CORPORATE IN	
ک ر	20	


PROJECT INFO:	MASSM/	
DRAW	/N BY:	SALES:
A	Author	
SMET	NO.:	SHEET:
22106		C1 2
ARCH	T. NO.:	G1.3
DATE	4/30/202	24 7:52:16 AM



WALL TYPE	STUD	SPACING	KEY NOTES
	DESIGNATION		
D.1	358S162-30	16" O.C.	1,2,3
D.2	600S162-54	16" O.C.	1,2,3

STRUCTURE ABOVE SLOTTED TOP TRACK FOR DEFLECTION DO NOT FASTEN GYP. BD. TO TOP TRACK OPTIONAL BATT INSULATION SEE KEY NOTES METAL STUDS 5/8" GYPSUM BOARD, **EACH SIDE** SEALANT - REFER TO WALL ASSEMBLY NOTES

STUD DESIGNATION	SPACING	MAX HEIGHT (5PSF, L/240)	KEY NOTES
150S162-30	16" O.C.	10' - 0"	1,2,3
362S162-30	16" O.C.	15' - 0"	1,2,3
600S162-30	16" O.C.	23' - 0"	1,2,3
	DESIGNATION 150S162-30 362S162-30	DESIGNATION SPACING 150S162-30 16" O.C. 362S162-30 16" O.C.	DESIGNATION SPACING (5PSF, L/240) 150S162-30 16" O.C. 10' - 0" 362S162-30 16" O.C. 15' - 0"




WALL TYPE	STUD DESIGNATION	SPACING	MAX HEIGHT (5PSF, L/240)	KEY NOTES
B.1	150S162-30	16" O.C.	10' - 0"	1,2,3
B.2	362S162-30	16" O.C.	15' - 0"	1,2,3
B.3	600S162-30	16" O.C.	23' - 0"	1,2,3

WALL TYPE D - (METAL STUD PARTITION)

WALL TYPE C - (METAL STUD PARTITION) 3 /A0.1 SCALE = 1 1/2" = 1'-0" 4 /A0.1 SCALE = 1 1/2" = 1'-0"

WALL TYPE B - (METAL STUD PARTITION) 2 /A0.1 SCALE = 1 1/2" = 1'-0"



EXT. WALL - 3 EXT. WALL - 4 7 /A0.1 SCALE = 1 1/2" = 1'-0" 8 /A0.1 SCALE = 1 1/2" = 1'-0"

26GA SEMI-CONCEALED

WALL PANEL PER PEMB

SUPPLIER

ZEE GIRT PER

PEMB SUPPLIER

FULL CAVITY WALL

INSUL. (MIN. R-25)

EXT. WALL - 2 6 /A0.1 SCALE = 1 1/2" = 1'-0"



WALL ASSEMBLY KEY NOTES

- INCLUDE FIBERGLASS SOUND INSULATION
- INCLUDE PAINTABLE ACOUSTIC SEALANT AT WALL BASE AND TOP TERMINATIONS, TYPICAL BOTH SIDES OF WALL (WHERE APPLICABLE).
- PROVIDE 1" GAP FOR DEFLECTION ALLOWANCE BETWEEN WALL FINISH/SUBSTRATE AND STRUCTURE ABOVE. TYPICAL UNLESS NOTED OTHERWISE ON CONSTRUCTION DOCUMENTS.


GENERAL WALL ASSEMBLY NOTES


LIGHT GAUGE STEEL FRAMING MEMBER DESIGNATION SYSTEM:

362S162-30 MINIMUM BASE METAL THICKNESS IN MILS. (EXAMPLE - .030 = 30 MILS) 30 = 20 GAUGE DRYWALL 33 = 20 GAUGE 43 = 18 GAUGE 54 = 16 GAUGE 68 = 14 GAUGE 97 = 12 GAUGE \ FLANGE WIDTH (1/100 INCHES) (EXAMPLE - 162 = 1.625") STYLE: S = STUD OR JOIST SECTION (WITH FLANGE STIFFENERS) = T = TRACK SECTION = L____ U = CHANNEL SECTION (STUDS WITHOUT FLANGE STIFFENERS) = F = FURRING CHANNEL = _____ Z = ZEE SECTION = ____


MEMBER DEPTH (1/100 INCHES) (EXAMPLE - 362 = 3-5/8")

- IN ALL WET AREAS SUCH AS SHOWERS AND TUBS, INSTALL CEMENT BASED BACKER BEHIND AREAS SCHEDULED TO RECEIVE TILE FINISH.
- ON ALL RESTROOM WALLS AND OTHER AREAS SCHEDULED TO RECEIVE FRP OR TILE FINISH, PROVIDE A MINIMUM OF MOISTURE-RESISTANT GYPSUM BOARD.
- ALL PARTITIONS CONTAINING PLUMBING OR HAVING AN EXTERIOR FACE SHALL BE INSULATED. WHERE GYPSUM BOARD EXTENDS TO UNDERSIDE OF STRUCTURE ABOVE, STOP GYPSUM BOARD
- 1/2" BELOW LINE OF STRUCTURE AND SEAL AS REQUIRED. REFERENCE FLOOR FINISH PLANS AND WALL FINISH PLANS FOR ADDITIONAL FINISHES NOT
- REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATIONS OF WALL PENETRATIONS.
- SEAL ALL OPENINGS WITH ACOUSTICAL SEALANT. PROVIDE FIRE-TREATED WOOD OR STEEL BACKING FROM ALL WALL MOUNTED FINISH CARPENTRY, ARCHITECTURAL WOODWORK, TOILET PARTITIONS, ACCESSORIES AND OTHER
- REFER TO STRUCTURAL DOCUMENTS FOR SHEAR WALL CRITERIA.





ROOF - 2 12 /A0.1 SCALE = 1 1/2" = 1'-0"



ROOF - 1 11 /A0.1 SCALE = 1 1/2" = 1'-0"

CONSTRUCTION (DESIGN. BUILD. F


MASSMAN CORPORATE INC

SALES: DRAWN BY: Author SHEET: SMET NO.:

DATE: 4/30/2024 7:52:16 AM

ARCHT. NO.:

A0.1



ARCHITECTURAL PLAN NOTES

1) ALL DIMENSION ARE FROM FACE OF STUD TO FACE OF STUD (U.N.O.)

3) ALL PLUMBING WALLS TO BE CONSTRUCTED OF 6" STUDS U.N.O. 4) SEE SHEETS A0.1, A2 & A3 FOR EXTERIOR WALL TYPES & MATERIALS

2) SEE A0.1 & A1.2 FOR ALL WALL TYPES & LOCATIONS

SALES: A1.0

MASSMAN CORPORATE INC

DATE: 4/30/2024 7:52:18 AM **SCALE**: 3/32" = 1'-0"

NORTH

FLOOR PLAN - OVERALL
1 /A1.0 SCALE = 3/32" = 1'-0"

8' - 1 1/4"

2

3

4

2 A3.1


124


125

TTT

BREAKROOM

128





DATE: 4/30/2024 7:52:19 AM

SCALE: As indicated

MASSMAN CORPORATE INC

ARCHITECTURAL PLAN NOTES

1) ALL DIMENSION ARE FROM FACE OF STUD TO FACE OF STUD (U.N.O.)

3) ALL PLUMBING WALLS TO BE CONSTRUCTED OF 6" STUDS U.N.O. 4) SEE SHEETS A0.1, A2 & A3 FOR EXTERIOR WALL TYPES & MATERIALS

2) SEE A0.1 & A1.2 FOR ALL WALL TYPES & LOCATIONS

160' - 0"

VESTIBULE

RECEPTION

STATION CORRIDOR

RESTROOM

119

JANITORS __

OFFICE 110

117

SHOP / WAREHOUSE 131

OFFICE

116

OFFICE

115

_CUBICLE AREA

109

OFFICE

113

112

APPROX. -LOCATION FIRE RISER

114

CONFERENCE


OFFICE 123

CORRIDOR 105

OFFICE 127

OFFICE

126



ARCHITECTURAL PLAN NOTES

1) ALL DIMENSION ARE FROM FACE OF STUD TO FACE OF STUD (U.N.O.)

3) ALL PLUMBING WALLS TO BE CONSTRUCTED OF 6" STUDS U.N.O. 4) SEE SHEETS A0.1, A2 & A3 FOR EXTERIOR WALL TYPES & MATERIALS

2) SEE A0.1 & A1.2 FOR ALL WALL TYPES & LOCATIONS

DATE: 4/30/2024 7:52:20 AM

MASSMAN CORPORATE INC.

SALES:

A1.2

FLOOR PLAN -OFFICE AREA DIMENSION PLAN


ARCHT. NO.:


SALES: DRAWN BY: Author SHEET: SMET NO.: A1.3 ARCHT. NO.: **DATE:** 4/30/2024 7:52:21 AM **SCALE**: 3/32" = 1'-0"


ROOF PLAN - OVERALL

1 /A1.3 SCALE = 3/32" = 1'-0"

NORTH







DATE: 4/30/2024 7:52:23 AM

MASSMAN CORPORATE INC

SALES:

SHEET:

SECTIONS
BUILDING

A3.0


SCALE: As indicated


DRAWN BY:


SMET NO.:

ARCHT. NO.:

Author









ROOF - 1

EAVE HEIGHT_ 128' - 0" RTU'S (SCREENED W/ACRYLICAP ABS PANEL

(FLAT PAN) or EQUIV.)
PER HVAC SUPPLIER
(F.V. SIZE / LOCATION /
WEIGHT OF EA. UNIT)

BUILDING SECTION - WAREHOUSE RESTROOMS

3 /A3.1 SCALE = 1/2" = 1'-0"

BUILDING SECTION - BREAKROOM


2 /A3.1 SCALE = 1/4" = 1'-0"


SM	DR	PROJECT INFO:				
ET N	AWN Aut		REV	REVISIONS		COPYRIGHT NOTICE:
O.:		MASSMAN	⋖	03.14.24	FINISHES	THIS DRAWING IS THE PROP
		CORPORATE INC	٥	04.29.24	R-VALUES / RTU'S	PURPOSE OF COMMUNICATI
SHE	SAL					EVALUATION AND CONSIDER WHOLE OR IN PART. IS NOT
EET	ES					EXPRESSED WRITTEN CONS
:):					CONSTRUCTION CORP. WE I
		VECTIONS -				SOLE DISCRETION TO REQU
		C N C				WHOLE UPON NOTICE, TOUR
						UNDERSTANDING AND ACCE


A3.1


ARCHT. NO.:


DATE: 4/30/2024 7:52:24 AM














CONSTRUCTION (DESIGN, BUILD, F

ၓ	≐ ∂	ว์ ธ ี เ	ú ≥ ′	ထဲ ပ	ິ ≥	2 5)
ONS							
REVISIONS							
<u> </u>							


MASSMAN CORPORATE INC

SCHEDULES -DOOR / WINDO SALES:

DRAWN BY: Author SHEET: SMET NO.: A6.0 ARCHT. NO.:

DATE: 4/30/2024 7:52:26 AM

SCALE: 1/4" = 1'-0"



FINISH PLAN LEGEND

P-1 WALL FINISH


B-1 **─** WALL BASE

FLOOR FINISH TRANSITION

FLOOR FINISH - F-1

INDICATES FLOOR ———

PATTERN DIRECTION



MASSMAN CORPORATE INC

Author

NORTH

FINISH PLAN - OVERALL
1/A6.1 SCALE = 3/32" = 1'-0"

SALES:

SHEET:

DATE: 4/30/2024 7:52:27 AM

SCALE: As indicated

A6.1


LP-1

CT-1 CTB-1 P-1

WOMEN'S

133 CT-1 CTB-1

FINISH PLAN - OFFICE AREA
1 /A6.2 SCALE = 1/8" = 1'-0"



MASSMAN CORPORATE INC SALES: DRAWN BY: Author SHEET: SMET NO.: A6.2 ARCHT. NO.: **DATE:** 4/30/2024 7:52:28 AM

CUBICLE AREA P-1 P-1 P-1 VB-1 109 CONC-2 VB-1 P-1 OFFICE VB-1 P-1 STORAGE 107 CORRIDOR CONC-2 P-1 WOMENS LVP-1 1 120 VB-1 P-1 OFFICE

112

CPT-1

VB-1

P-1 115 CPT-1 VB-1 P-1 | CPT-1 | VB-1 | P-1 | 125 CPT-1 VB-1 P-1 | CPT-1 | VB-1 | P-1 | VB-1 P-1 MENS | LVP-1 | VB-1 | P-1 | RESTROOM LP-1 119 LVP-1 VB-1 P-1 JANITORS

118

LVP-1

VB-1

P-1

FRP-1 4'-0" A.F.F.

@ MOP SINK LP-1 BREAKROOM 128 CONC-2 VB-1 P-1

RECEPTION 111 CPT-1 CONFERENCE VB-1 / CPT-1 108 CPT-1 CPT-1 CONC-2 VB-1 CUBICLE

122

CONC-2

VB-1


P-1

LP-1

FINISH PLAN LEGEND FLOOR FINISH TRANSITION P-1 WALL FINISH B-1 WALL BASE FLOOR FINISH - F-1 INDICATES FLOOR ——— PATTERN DIRECTION

			ROOI	M FINISH LEGEN	ID		
	LOCATION	MARK	FINISH	MANUFACTURER	STYLE	COLOR	REMARKS
	FLOORING	CPT-1	CARPET TILE	VERIFY	VERIFY	VERIFY	
	FLOORING	CT-1	CERAMIC TILE	VERIFY	VERIFY	VERIFY	
	FLOORING	LVP-1	LUXURY VINYL PLANK	VERIFY	VERIFY	VERIFY	
^ ^	ELOORING	CQNC-1	CONCRETE	VERIFY	VERIEY	VERIFY	
<u> </u>	FLOORING	CONC-2	POLISHED CONCRETE	VERIFY	VERIFY	VERIFY)
·	WALL	P-1	PAINTED DRYWALL	VERIFY	LEVEL 4 - SMOOTH	VERIFY	
	WALL	FRP-1	SMOOTH	VERIFY	VERIFY	VERIFY	1/2" GYP BD BACKI
	WALL	LP-1	LINER PANEL	VERIFY	VERIFY	WHITE	
	WALL	IMP-1	INTERIOR FINISH SIDE OF IMP	VERIFY	SMOOTH	VERIFY	
INISH	WALL	BLS-1	BANDED LINER SYSTEM	VERIFY	VERIFY	WHITE	
ПИІЗП	WALL BASE	VB-1	4" VINYL BASE	VERIFY	4" TALL	VERIFY	
	WALL BASE	CTB-1	CERAMIC TILE	VERIFY	4" TALL	VERIFY	

	COLOR	REMARKS
	VERIFY	
	VERIFY	
	VERIFY	
~~	VEBLEY	
 	VERIFY)
OTH	VERIFY	
	VERIFY	1/2" GYP BD BACKER
	WHITE	
	VERIFY	
	WHITE	
	VERIFY	
	1	I



DATE: 4/30/2024 7:52:29 AM **SCALE**: 3/32" = 1'-0"

SALES:

SHEET:

A6.3

MASSMAN CORPORATE INC

DRAWN BY:

SMET NO.:

ARCHT. NO.:

NORTH

RCP - OVERALL

1 /A6.3 SCALE = 3/32" = 1'-0"

Author

REFLECTED CEILING PLAN -PROPOSED

PRE-ENGINEERED METAL BUILDING

- THE ENTIRE PRE-ENGINEERED METAL BUILDING SYSTEM SHALL BE DESIGNED BY THE METAL BUILDING MANUFACTURER IN CONFORMANCE TO THE PROVISIONS OF THE INTERNATIONAL BUILDING CODE AND THE METAL BUILDING SYSTEMS MANUAL AS PUBLISHED BY THE METAL BUILDING MANUFACTURER'S ASSOCIATION. WHERE THESE CRITERIA CONFLICT, THE MORE STRINGENT CRITERIA SHALL APPLY.
- IT IS THE PRE-ENGINEERED MANUFACTURER'S RESPONSIBILITY TO DESIGN THE COMPLETE BUILDING SYSTEM (STEEL FRAMING, COMPONENTS, ATTACHMENTS, ETC.) THE MANUFACTURER SHALL SUBMIT A CERTIFICATION LETTER BEARING THE SEAL OF A PROFESSIONAL ENGINEER STATING THAT THE BUILDING SYSTEM DESIGN MEETS THE INDICATED CODE, PERFORMANCE AND LOADING REQUIREMENTS.
- THE PRE-ENGINEERED METAL BUILDING MANUFACTURER SHALL BE CERTIFIED BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION, CATEGORY MB. THE MANUFACTURER SHALL MEET THE EXCEPTION NOTED PER THE IBC WHICH SPECIFIES QUALITY CONTROL REQUIREMENTS OF THE MANUFACTURER PERTAINING TO SPECIAL
- THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF THE ENTIRE METAL BUILDING SYSTEM FOR REVIEW. THE CONTRACTOR SHALL ALSO SUBMIT A COMPLETE STRUCTURAL DESIGN ANALYSIS OF THE BUILDING SYSTEM
- FOR RECORD PURPOSES ONLY. THE SHOP DRAWING SUBMITTAL SHALL INCLUDE ALL FOUNDATION REACTIONS. ALL SHOP DRAWINGS AND CALCULATION SUBMITTALS SHALL BEAR THE SEAL OF A PROFESSIONAL ENGINEER. DESIGN LOADS TO BE USED IN CONNECTION WITH THE METAL BUILDING DESIGN ARE PER THE DESIGN LOADS CRITERIA. COORDINATE ANY EQUIPMENT LOADS WITH THE MECHANICAL, ELECTRICAL AND ARCHITECTURAL
- CALCULATIONS FOR FRAME DEFLECTIONS SHALL BE DONE USING ONLY THE BARE FRAME METHOD. DRIFT SHALL FOLLOW AISC'S "SERVICEABILITY DESIGN CONSIDERATIONS FOR LOW-RISE BUILDINGS." CALCULATIONS SHALL BE SUBMITTED VERIFYING THE ACTUAL DRIFT UNDER CODE REQUIRED LOADINGS DOES NOT EXCEED THE
- THE PRE-ENGINEERED MANUFACTURER SHALL PROVIDE ALL GIRTS, PURLINS, FRAMES AND OTHER COMPONENTS REQUIRED FOR A COMPLETE SYSTEM. ALL WALL SYSTEMS, SUCH AS METAL STUDS, STOREFRONTS, ETC. SHALL BE PROPERLY SUPPORTED BY THE METAL BUILDING SYSTEM. ALLOWABLE DEFLECTIONS OF
- COMPONENTS SHALL BE IN ACCORDANCE WITH THE IBC. THE FOUNDATION DESIGN IS BASED UPON THE PRE-ENGINEERED METAL BUILDING REACTIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF ANY REVISIONS REQUIRED AS A RESULT OF CHANGE IN THE BUILDING MANUFACTURER, INCLUDING REDESIGN OF THE FOUNDATIONS.
- THE DIAMETER, NUMBER AND PLACEMENT PATTERN OF ALL ANCHOR BOLTS SHALL BE DETERMINED BY THE PRE-ENGINEERED BUILDING MANUFACTURER. ANCHOR BOLT EMBEDMENTS ARE INDICATED ON THE STRUCTURAL DRAWINGS.
- THE PRE-ENGINEERED METAL BUILDING SHALL BE DESIGNED BY THE MANUFACTURER TO RESIST LATERAL LOADS
- INTERIOR FRAME LINES: RIGID FRAMES
- PERIMETER WALL LINES: BRACED BAYS OR PORTAL FRAMES.
- THE METAL BUILDING ERECTOR SHALL PROVIDE ALL TEMPORARY BRACING.
- UNLESS NOTED OTHERWISE OR SPECIFIED, ALL STEEL MEMBERS SHALL BE CLEANED AND PAINTED IN ACCORDANCE WITH THE MANUFACTURER'S STANDARD PROCEDURES.
- REFER TO ARCHITECTURAL PLANS AND SPECIFICATIONS FOR SPECIFIC DESIGN INFORMATION FOR ROOF PANELS, WALL PANELS, ROOF INSULATION AND WALL INSULATION.

OPEN-WEB STEEL JOISTS

- SHOP DRAWINGS INDICATE CONFIGURATION, SIZES, SPACING, LOCATIONS OF JOISTS, BRIDGING AND C CONNECTIONS
- PERFORM WORK IN ACCORDANCE WITH SJI
- MATERIALS ARE AS FOLLOWS:
- OPEN-WEB JOISTS: ASTM A36
- ANCHOR BOLTS, NUTS, AND WASHERS: ASTM A307 GRADE A, ASTM A563 FOR ATTACHMENT TO WOOD BEARING PLATES 3. BRIDGING: ASTM A36
- ALLOW FOR ERECTION LOADS. PROVIDE TEMPORARY BRACING TO MAINTAIN FRAMING IN ALIGNMENT UNTIL
- COMPLETION FOR ERECTION AND INSTALLATION OF PERMANENT BRIDGING AND BRACING. AFTER JOIST ALIGNMENT, SECURE JOISTS TO BEARING SURFACES.
- FRAME ROOF OPENINGS GREATER THAT 18" WITH SUPPLEMENTARY FRAMING.
- AFTER ERECTION, PRIME WELDS, ABRASIONS, AND SURFACES NOT SHOP PRIMED.
- UNLESS NOTED OTHERWISE, JOIST CONNECTIONS SHALL BE MADE PER JOIST SUPPLIER STANDARD
- LIVE LOAD DEFLECTIONS SHALL NOT EXCEED L/360 FOR FLOORS, L/360 FOR ROOFS WITH DIRECTLY APPLIED PLASTER CEILING FINISHES, OR L/240 FOR ROOF WITH ALL OTHER CEILING FINISHES.
- JOIST AND JOIST GIRDERS SHALL BE FIELD ATTACHED W/ A MINIMUM OF LISTED VALUES: K-SERIES JOISTS: (2) 1/8" FILLET WELDS x 2 1/2" LONG EACH SIDE OF JOIST SEAT, OR BOLTED w/ (2)
 - 1/2" Ø BOLTS IN SLOTTED HOLES PARALLEL TO JOISTS AT COLUMNS. LH-SERIES JOISTS, SECTION NUMBERS 02 THRU 06: (2) 3/16" FILLET WELDS x 2 1/2" LONG EACH SIDE
 - OF JOIST SEAT, OR BOLTED w/ (2) 3/4" Ø BOLTS IN SLOTTED HOLES PARALLEL TO JOISTS AT COLUMNS. 3. LH-SERIES AND DLH-SERIES JOISTS, SECTION NUMBERS 07 THRU 16: (2) 1/4" FILLET WELDS x 2 1/2" LONG EACH SIDE OF JOIST SEAT, OR BOLTED w/ (2) 3/4" Ø BOLTS IN SLOTTED HOLES PARALLEL TO
 - 4. DHL-SERIES JOISTS, SECTION NUMBERS 17-25: (2) 1/4" FILLET WELDS x 4" LONG EACH SIDE OF JOIST SEAT, OR BOLTED w/ (2) 3/4" Ø BOLTS IN SLOTTED HOLES PARALLEL TO JOISTS AT COLUMNS.
 - JOIST GIRDERS: (2) 1/4" FILLET WELDS x 4" LONG EACH SIDE OF JOIST SEAT, OR BOLTED w/ (2) 3/4" \emptyset BOLTS IN SLOTTED HOLES PARALLEL TO JOISTS AT GIRDER COLUMNS.

STEEL DECKING

- DESIGN OF METAL DECKING IN ACCORDANCE WITH SDI MANUAL.
- MATERIALS ARE AS FOLLOWS:
- METAL DECK: AS INDICATED ON THE CONSTRUCTION DOCUMENT DETAILS. FASTENERS: MILD STEEL WELD WASHERS, HARDENED STEEL SELF-TAPPING SCREWS OR POWDER
- ACTUATED FASTENERS. BEAR DECKING ON WOOD SUPPORT SURFACES WITH A 4" MINIMUM BEARING AND ON STEEL SUPPORTS WITH A
- MINIMUM OF 1-1/2" BEARING. FASTEN RIBBED DECK TO STEEL SUPPORT MEMBERS AT ENDS AND INTERMEDIATE SUPPORTS WITH FUSION WELDS THROUGH WASHERS OR MECHANICAL FASTENERS AT 12" O.C. AND AT EVERY OTHER TRANSVERSE FLUTE,
- REINFORCE STEEL DECK OPENINGS FROM 6" TO 18" IN SIZE WITH 2"x2"x1/4" STEEL ANGLES. LARGER OPENINGS SEE DRAWINGS.
- UNLESS INDICATED OTHERWISE, PROVIDE 3"x3"x3/16" DECK SUPPORT ANGLES AROUND PERIMETER OF ROOF

STRUCTURAL STEEL CONSTRUCTION


- A. SPECIFICATIONS:
 - DESIGN, FABRICATION, AND ERECTION OF STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH THE 14TH EDITION OF THE "STEEL CONSTRUCTION MANUAL", BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION, UNLESS NOTED OTHERWISE.
 - STEEL MATERIALS SHALL MEET THE REQUIREMENTS OF THE FOLLOWING SPECIFICATIONS, UNLESS NOTED OTHERWISE:

STRUCTURAL TYPE/SHAPE	ASTM DESIGNATION	MATERIAL STRENGTH
ANCHOR BOLTS	F1554 GRADE 36	Fy = 36 KSI
W-SHAPE	A992	Fy = 50 KSI
M, S, C, MC, AND L-SHAPES, PLATES AND BARS	A36	Fy = 36 KSI
HP-SHAPE	A572 GRADE 50	Fy = 50 KSI
PIPES	A53 GRADE B	Fy = 35 KSI
HSS RECTANGULAR	A500 GRADE B	Fy = 46 KSI
HSS ROUND	A500 GRADE B	Fy = 42 KSI
FASTENERS	A325N	Fnv = 48 KSI, Fnt = 90 KSI
	A325X	Fnv = 60 KSI, Fnt = 90 KSI
	A490N	Fnv = 60 KSI, Fnt = 113 KSI
	A490X	Fnv = 75 KSI, Fnt = 113 KSI
CONNECTION NUTS	A563	
WASHERS	F436	
WELDS		
E70XX ELECTRODES	A233	Fu = 70 KSI
COLD ROLLED E60XX ELECTRODES	A233	Fu = 60 KSI
STUD ANCHORS	A108	Fu = 65 KSI

- ALL ASTM A325 BOLTS EXPOSED TO EXTERIOR CONDITIONS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A123; ASTM 490 BOLTS SHALL NOT BE GALVANIZED.
- PROVIDE 2 MIL. THICK OXIDE PRIMER ON ALL STEEL SURFACES UNLESS NOTED OTHERWISE
- **DESIGN STRESS:**
- MINIMUM BEAM CONNECTIONS SHALL NOT BE SMALLER THAN THOSE LISTED IN PART 10 OF THE AISC
- UNLESS DETAILED OTHERWISE, MAKE CONNECTIONS WITH E70XX ELECTRODES OR BOLTED WITH 3/4" A325 BOLTS IN BEARING-TYPE CONNECTIONS WITH THREADS IN THE SHEAR PLANE (A325N).
- WELDING:
- ALL WELDING SHALL CONFORM TO THE REQUIREMENTS OF AWS D1.1 STRUCTURAL WELDING CODE. WELDER CERTIFICATION PROCEDURES SHALL BE AS FOLLOWS: a. ALL WELDERS SHALL BE CURRENTLY CERTIFIED AN REGISTERED BY THE LOCAL OFFICIALS
- AND/OR THE AMERICAN WELDING SOCIETY AND, IF REQUIRED, ALL WELDERS SHALL HAVE THEIR CERTIFICATION AVAILABLE TO THE ENGINEER.
- ALL BUTT WELDS SHALL BE COMPLETE JOINT PENETRATION (CJP) WELDS, UNLESS NOTED OTHERWISE. ALL GROVE WELDS SHALL BE COMPLETE JOINT PENETRATION (CJP) WELDS, UNLESS NOTED OTHERWISE.
- WELDING PROCEDURE AND SEQUENCES SHALL BE PLANNED TO MINIMIZE WELD SHRINKAGE THAT COULD RESULT IN LAMELLAR TEARING
- FIELD WELDING WILL BE ALLOWED ONLY WHERE SHOWN ON DRAWINGS. EXISTING AND NEW STEEL SURFACES TO BE WELDED SHALL BE CLEANED OR PAINT, GREASE, SCALE, OR
- OTHER FOREIGN MATERIAL REMOVED.
- ALL FIELD WELDS SHALL BE WIRE BRUSHED AND CLEANED, THEN TOUCHED-UP PAINTED.

COLD-FORMED STEEL CONSTRUCTION

- DESIGN COLD FORMED STEEL FRAMING ACCORDING TO AISI'S "STANDARD FOR COLD-FORGED STEEL FRAMING -GENERAL PROVISIONS."
- MATERIALS:
- ALL MEMBERS SHALL BE COLD-FORMED FROM STRUCTURAL QUALITY SHEET STEEL MEETING THE REQUIREMENTS OF ASTM A-446 GRADE A, MINIMUM YIELD OF 33,000 PSI FOR 18 GAUGE AND LIGHTER AND MEETING THE REQUIREMENTS OF ASTM A-446 GRADE D, MINIMUM YIELD OF 50,000 PSI FOR 16
- ALL MEMBERS SHALL BE MARKED SO THAT SUPPLIED MATERIALS CAN BE FIELD VERIFIED. 3. ALL MEMBERS SHALL HAVE A GALVANIZED FINISH COMPLYING WITH ASTM A-535, G60 COATING.
- CONNECTIONS: WELDS: WELDING SHALL BE IN CONFORMANCE WITH AWS D 1.3 UTILIZING E60XX OR E70XX
- SCREWS: SELF-DRILLING AND SELF-TAPPING, CADMIUM PLATED FOR ALL EXTERIOR USES, OF THE SIZE REQUIRED FOR LOADINGS.
- POWER DRIVEN SHOTS: SIZE AND SPACING AS REQUIRED TO PROPERLY ANCHOR THE FRAMING MEMBERS. USE CHARGE AS APPROPRIATE FOR ACTUAL USE. WIRE TYING: NOT PERMITTED.
- LIGHT GAUGE STEEL FRAMING MEMBER DESIGNATION SYSTEM:



- MEMBER DEPTH (1/100 INCHES) (EXAMPLE - 362 = 3-5/8")

CAST-IN-PLACE CONCRETE

- ALL DESIGN AND CONSTRUCTION OF CAST-IN-PLACE CONCRETE SHALL CONFORM TO THE LATEST EDITION OF ACI 318 BUILDING CODE AND CRSI MANUAL OF STANDARD PRACTICE.
- CONCRETE SHALL BE STANDARD WEIGHT MIX UNLESS NOTED OTHERWISE AND MEET THE FOLLOWING CRITERIA:

LOCATION	f'c @ 28 DAYS	AIR ENTRAINMENT	MAX WATER/CEMENT RATIO
FOOTINGS/FOUNDATIONS	3500 PSI		0.55
WALLS	3500 PSI		0.55
FLOORS ON GRADE	4000 PSI		0.55
EXTERIOR SLABS ON GRADE	4000 PSI	6% ± 1.5%	0.45
EXPOSED EXTERIOR WALLS	4000 PSI	6% ± 1.5%	0.45

- PROTECT FOUNDATION EXCAVATIONS FROM FROST; CONCRETE PLACED IN FROST IS NOT PERMISSIBLE.
- DESIGN FROST PENETRATION DEPTH SHALL BE 48". FOUNDATION EXCAVATIONS SHALL BE KEPT FREE OF LOOSE MATERIAL AND STANDING WATER.
- MINIMUM OF 6" COMPACTED GRANULAR SUBGRADE BELOW SLABS. IF GEOTECHNICAL REPORT AVAILABLE USE MOST STRINGENT SUBGRADE.
- PLACE VAPOR RETARDER OR VAPOR BARRIER DIRECTLY BELOW SLABS ON GRADE.
- CEMENT SHALL CONFORM TO ASTM C150, TYPE I / II OR ASTM C595 TYPE IL. ADMIXTURES MAY BE USED WITH PRIOR APPROVAL OF THE ENGINEER. CALCIUM CHLORIDE SHALL NOT BE USED. ADMIXTURES SHALL COMPLY WITH ASTM C494 AND BE OF A TYPE THAT INCREASES THE WORKABILITY OF THE
- ALL MIXES SHALL BE DESIGNED AND CERTIFIED BY A MATERIALS TESTING COMPANY. CONCRETE FLOOR SHALL BE CURED IN ACCORDANCE WITH ASTM C309. CONCRETE FLOOR SHALL BE PROTECTED FROM MOISTURE FOR A MINIMUM OF 14 DAYS WITH AN APPROVED SHEET MEMBRANE IN ACCORDANCE WITH
- POST-INSTALLED ANCHORS ONLY ALLOWED WITH THE APPROVAL AND REVIEW OF ENGINEER OF RECORD. MINIMUM DEVELOPMENT LENGTH OF REINFORCING BARS SHALL BE AS FOLLOWS UNLESS NOTED OTHERWISE:

MINI	MUM LENG	TH FOR S	TANDARD U	IN-COATED	BARS IN NORMAL WEIG	HT CONCRETE
	DEVELOPI	MENT LEN	GTH (Ld) FC	OR STRAIGI	HT BARS (MIN 12")	500 00° H00K50
CONCRETE	TENSION	CLASS A	TENSION	CLASS B	COMPRESSION	FOR 90° HOOKED BARS, HOOK
STRENGTH f'c IN PSI	#6 & SMALLER	#7 TO #11	#6 & SMALLER	#7 TO #11	#18, #14, & #11 AND SMALLER	DEVELOPMENT LENGTH
3000	44 Db	55 Db	57 Db	71 Db	30 Db	22 Db
3500	41 Db	51 Db	53 Db	66 Db	30 Db	20 Db
4000	38 Db	47 Db	49 Db	62 Db	30 Db	19 Db
4500	36 Db	45 Db	47 Db	58 Db	30 Db	18 Db
5000	34 Db	42 Db	44 Db	55 Db	30 Db	17 Db

TYPICAL SPLICES: CLASS B AS DEFINED IN ACI 318, UNLESS NOTED OTHERWISE. MINIMUM CLEAR CONCRETE COVER FOR REINFORCING STEEL TO MEET THE FOLLOWING CRITERIA:

MINIMUM CLEAR CONCRETE COVER FOR REINFORCII	NG STEEL
CONCRETE ON SOIL (DIRECT CONTACT)	3"
SLAB ON GRADE	CENTERED
WALLS, STRUCTURAL SLABS EXPOSED TO SOIL OR WEATHER	
#6 TO #18 REBAR	2"
#5 AND SMALLER REBAR	1-1/2"
WALLS, STRUCTURAL SLABS NOT EXPOSED TO EARTH OR WEATHER	
#11 AND SMALLER REBAR	3/4"
COLUMNS AND PIERS (COVER TO STIRRUPS AND TIES)	1-1/2"

- REINFORCING STEEL, ANCHOR BOLTS, AND DOWELS SHALL BE SECURED WITH WIRE POSITIONERS, OR EQUIVALENT, BEFORE PLACING CONCRETE OR GROUT
- BARS TO BE WELDED SHALL BE ASTM A706, GRADE 60. WELDING OF REINFORCING BARS SHALL CONFORM TO ALL REINFORCEMENT PLACED IN FOUNDATION WALLS, FOOTINGS, PIERS, AND RETAINING WALLS SHALL BE HOT
- GALVANIZED REINFORCEMENT THAT HAS DAMAGED GALVANIZING SHALL BE FIELD DRESSED WITH (2) COATS OF
- COLD GALVANIZING PAINT. PROVIDE FROST PROTECTION OF SHALLOW FOUNDATION WITH INSULATION MEETING THE MINIMUM R VALUE, EXTENT AND DEPTH REQUIRED BY ASCE 32 FOR THIS BUILDING SITE. OTHERWISE, PROVIDE NON-FROST-SUSCEPTIBLE SOIL (AS DEFINED BY GRANULAR SOILS OR OTHER APPROVED NON-FROST SUSCEPTIBLE FILL
- MATERIAL WITH LESS THAN 6% OF MASS PASSING A #200 MESH SIEVE) DOWN TO ANTICIPATED FROST DEPTH, OR OTHER ACCEPTABLE MEANS. FOUNDATIONS PLACED ON A LAYER OF WELL-DRAINED, UNDISTURBED GROUND OR FILL MATERIAL THAT IS NOT DEPTH DEFINED IN SECTION 3.2. UNDISTURBED GRANULAR SOILS OR FILL MATERIAL WITH LESS THAN 6% OF
- SUSCEPTIBLE TO FROST SHALL HAVE THE THICKNESS OF SUCH A LAYER INCLUDED IN MEETING THE DESIGN FROST MASS PASSING A #200 (0.074 MM) MESH SIEVE IN ACCORDANCE WITH ASTM D422 AND OTHER APPROVED NON-FROST-SUSCEPTIBLE MATERIALS SHALL BE CONSIDERED NON-FROST-SUSCEPTIBLE. CLASSIFICATION OF FROST SUSCEPTIBILITY OF SOIL SHALL BE DETERMINED BY A SOILS OR GEOTECHNICAL ENGINEER, UNLESS OTHERWISE

REINFORCED MASONRY CONSTRUCTION

- ALL DESIGN AND CONSTRUCTION OF REINFORCED MASONRY CONSTRUCTION SHALL CONFORM TO THE FOLLOWING CODES:
 - ACI 530.1 / ASCE 7 / TMS 602 SPECIFICATION FOR MASONRY STRUCTURES ACI 530 / ASCE 7 / TMS 402 BUILDING CODE REQUIREMENTS FOR MASONRY STRUCTURES
- TYPICAL MATERIALS ARE AS FOLLOWS:

TYPE	STANDARD	GRADE
CONCRETE MASONRY BLOCK	ASTM C-90	2,800 PSI
TYPE M/S MORTAR	ASTM C-90	
GROUT (28 DAY STRENGTH)	ASTM C-90	2,000 PSI
REINFORCING BARS	ASTM A615 Gr 60	Fy = 60 KSI

- THE REQUIRED MINIMUM 28 DAY COMPRESSIVE STRENGTH OF THE COMBINATION OF CONCRETE BLOCK, GROUT AND MORTAR ON THE NET AREA OF CONSTRUCTION (f'm) SHALL BE LAID IN RUNNING BOND, UNLESS NOTED OTHERWISE.
- ALL CONCRETE BLOCK MASONRY UNITS SHALL BE LAID IN RUNNING BOND, UNLESS NOTED OTHERWISE. MASONRY BLOCK CELLS CONTAINING VERTICAL REINFORCING SHALL BE GROUTED SOLID. FILLING CELLS WITH
- MORTAR IS NOT ACCEPTABLE.
- THE BASE OF EACH CELL IN WHICH REINFORCING BAR IS PLACED MUST HAVE A CLEAN OUT HOLE. VERTICAL REINFORCING BARS SHALL BE LAPPED PER SCHEDULE. PROVIDE CONTINUOUS REINFORCED BOND-BEAMS IN ALL REINFORCED MASONRY WALLS AT THE TOP, AND AS
- FILL CORES OF MASONRY UNDER ALL BEARING PLATES. THE MINIMUM WIDTH SHALL BE 3 TIMES THE BEARING PLATE LENGTH FOR THREE COURSES BELOW BEARING, UNLESS NOTED OTHERWISE.

JOINTS. BOND-BEAM REINFORCING SHALL EXTEND INTO AND BE CONTINUOUS WITH ALL INTERSECTING

REQUIRED IN CONSTRUCTION DOCUMENTS. BOND-BEAMS AT THE TOP OF THE WALL SHALL BE CONTINUOUS AT MASONRY CONTROL JOINTS. ALL OTHER BOND-BEAMS SHALL NOT BE CONTINUOUS AT MASONRY CONTROL

REINFORCED MASONRY WALLS SHALL HAVE #9 GAUGE (LADDER TYPE) HORIZONTAL REINFORCING AT SPACING AS NOTED ON CONSTRUCTION DOCUMENTS, BUT AT A MAXIMUM OF 16" O.C. VERTICALLY. **VENEER LINTEL SUPPORT AS FOLLOWS:**


SPAN	MEMBER	BEARING
7' - 4"	L3-1/2" x 3-1/2" x 5/16" LLV	6"
9' - 0"	L5" x 3-1/2" x 5/16" LLV	8"
10' - 0"	L6" x 3-1/2" x 5/16" LLV	8"
12' - 0"	L6" x 4" x 5/16" LLV	8"
14' - 0"	L7" x 4" x 5/16" LLV	8"
16' - 0"	L8" x 4" x 1/2" LLV	8"


SSMAN RPORATE

SALES: DRAWN BY: Author SHEET: **SMET NO.:** ARCHT. NO.:

DATE: 4/30/2024 7:52:29 AM

SCALE: 12" = 1'-0"





PRE-ENGINEERED METAL BUILDING FLOOR PLAN TO BE INSERTED OWEE INFORMATION IS RECEIVED

MASSMAN CORPORATE INC.

DRAWN BY: Author

SMET NO.:

ARCHT. NO.:

SCALE:

SALES:


SHEET:

DATE: 4/30/2024 7:52:31 AM

S1.2

ANCHOR BOLT PLAN

SMET CONSTRUCTION SERVICE CORP. DESIGN. BUILD. FINANCE.



COPYRIGHT	THIS DRAWIN	PURPOSE OF	WHOLE OR IN	EXPRESSED CONSTRUCTI	SOLE DISCRE WHOLE UPOI	POSSESSION UNDERSTANI	
S							
REVISIONS							
R E							

DRAWN BY:

SMET NO.:

ARCHT. NO.:

Author

SALES:

SHEET:

DATE: 4/30/2024 7:52:31 AM

SCALE: 3/4" = 1'-0"

S1.3


THIS DRAWING IS THE PRO	PURPOSE OF COMMUNICA	WHOLE OR IN PART, IS NO	CONSTRUCTION CORP. WE	SOLE DISCRETION TO REC	POSSESSION OF THE PRO UNDERSTANDING AND ACC	


SMET CONSTRUCTION SERVICE CORP. DESIGN. BUILD. FINANCE.


PIER SCHEDULE								
8.4.4.DU	SIZE		VEDTICAL DEINE		DEINE TOD VIEW			
MARK	WIDTH	LENGTH	VERTICAL REINF.	HORIZONTAL TIES	REINF. TOP VIEW	REMARKS		
P7	16"	18"	(6) #5	#3 @ 12" O.C.	TYPE B			
P10	16"	24"	(8) #5	#3 @ 12" O.C.	TYPE C			
P50	24"	24"	(8) #5	#3 @ 12" O.C.	TYPE D			
P51	16"	32"	(8) #5	#3 @ 12" O.C.	TYPE C			
P52	18"	32"	(8) #5	#3 @ 12" O.C.	TYPE D			

CONCRETE PIER SCHEDULE NOTES:

- SEE FOUNDATION PLAN FOR TOP OF PIER ELEVATIONS
- SEE CAST-IN-PLACE SPECIFICATIONS FOR MATERIAL SPECIFICATIONS
- SEE ANCHOR BOLT PLAN AND DETAILS FOR COLUMN ANCHOR BOLT INFORMATION
- VERTICAL REINF. BARS SHALL BE EQUALLY SPACED, U.N.O. HORIZONTAL TIES SHALL MEET REQ'S OF ACI 318-7.10.5.3 FOR LATERAL SUPPORT OF VERTICAL REINFORCING









SPREAD FOOTING SCHEDULE									
		FOOTING SIZE		REINFORCEM	REINFORCEMENT - LONG BARS		REINFORCEMENT - SHORT BARS		
MARK	LENGTH	WIDTH	DEPTH	воттом	ТОР	воттом	ТОР	Remarks	
F3	3' - 0"	3' - 0"	12"	(4) #4	-	(4) #4	-		
F4	4' - 0"	4' - 0"	12"	(4) #5	-	(4) #5	-		
F5.5	5' - 6"	5' - 6"	14"	(6) #5	-	(6) #5	-		

SPREAD FOOTING SCHEDULE NOTES:

- SEE FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS
- SEE CAST-IN-PLACE SPECIFICATIONS FOR MATERIAL SPECIFICATIONS
- SEE ANCHOR BOLT PLAN AND DETAILS FOR COLUMN ANCHOR BOLT INFORMATION


SECTION VIEW






CONTINUOUS FOOTING SCHEDULE NOTES:

- ALL FOOTINGS ARE CENTERED ON FOUNDATION WALLS UNLESS DIMENSIONED OTHERWISE ON PLANS
- SEE CAST-IN-PLACE SPECIFICATIONS FOR MATERIAL SPECIFICATIONS
- SEE CAST-IN-PLACE SPECIFICATIONS FOR MATERIAL SPECIFICATIONS
- SEE FOUNDATION PLAN FOR TOP OF FOOTING ELEVATIONS






CONCRETE FROST WALL SCHEDULE NOTES:

- SEE FOUNDATION PLAN FOR TOP OF WALL & LEDGE (IF APPLICABLE) ELEVATIONS
- SEE CAST-IN-PLACE SPECIFICATIONS FOR MATERIAL SPECIFICATIONS
- DOCK WALLS TO BE REFERENCED ON PLAN ACCORDINGLY

THIS DETAIL IS FOR FROST WALLS ONLY. FOR RETAINING WALLS SEE






MASSMAN CORPORATE INC

SALES: DRAWN BY: Author SHEET: SMET NO.: S2.0 ARCHT. NO.:

SCALE: As indicated


FOUNDATI SCHEDULE DETAILS

DATE: 4/30/2024 7:52:32 AM





SLAB THICKNESS CHANGE DETAIL

4 /S2.1 SCALE = 3/4" = 1'-0"




BOLLARD DETAIL 8/S2.1 SCALE = 3/4" = 1'-0"






STOOP DIMENSIONS AT SERVICE DOORS

12 /S2.1 SCALE = 1/2" = 1'-0"




FOOTING STEP

3 /S2.1 SCALE = 3/4" = 1'-0"



WALL VERTICAL CONST. JOINT


7 /S2.1 SCALE = 3/4" = 1'-0"



- PLACE EXPANSION JOINT WHERE WALK ABUTS BUILDING DEPRESS TOP BELOW SURFACE OF SLAB & SEAL WITH COLD POURED SILICONE WYPE JOINT SEAL.
- UNLESS OTHERWISE NOTED ON THE PLANS ALL SIDEWALKS SHALL HAVE A MAX CROSS SLOPE OF 2%.


INTEGRAL CONCRETE CURB & SIDEWALK DETAIL

11 /S2.1 SCALE = 3/4" = 1'-0"




HAIRPIN-HP1

2 /S2.1 SCALE = 3/4" = 1'-0"




FOOTING CORNER REINFORCEMENT

6 /S2.1 SCALE = 3/4" = 1'-0"




REBAR @ ALL DOOR OPENINGS

10 /S2.1 SCALE = 3/4" = 1'-0"




CONCRETE ENCASED ELECTRODE FROST WALL

1 /S2.1 SCALE = 1/8" = 1'-0"




WALL CORNER REINFORCEMENT DOUBLE MAT

5 /S2.1 SCALE = 3/4" = 1'-0"



APRON DETAIL




DOOR KNOCK-OUT DETAIL

SALES: DRAWN BY: Author SHEET: SMET NO.: S2.1 ARCHT. NO.: **DATE:** 4/30/2024 7:52:33 AM


SCALE: As indicated

MASSMAN CORPORATE INC FOUNDATION DETAILS

13 /S2.1 SCALE = 3/4" = 1'-0"




DOCK LEVELER (LONGITUDINAL) CROSS SECTION 3 /S2.2 SCALE = 1/2" = 1'-0"




DOCK LEVELER CROSS SECTION

2 /S2.2 SCALE = 1/2" = 1'-0"




10" x 8'-0" LOADING DOCK RETAINING WALL

5 /S2.2 SCALE = 3/4" = 1'-0"




DOCK LEVELER PLAN VIEW

1 /S2.2 SCALE = 1/2" = 1'-0"



8" x 8'-0" DOCK WALL DETAIL

4 /S2.2 SCALE = 3/4" = 1'-0"



MASSMAN CORPORATE INC FOUNDATION DETAILS DRAWN BY: SALES: Author SHEET:


S2.2


DATE: 4/30/2024 7:52:33 AM

SCALE: As indicated


SMET NO.:


ARCHT. NO.:






FRAMING PLAN - SHOP RESTROOMS
3 /S3.0 SCALE = 1/2" = 1'-0"









PROJECT INFO:	MASSMAN		FRAMING PLA	STANDALONE	MEZZANINE
DRAWI	N BY: uthor	SALES):		
SMET 1	NO.:	SHEET	:		
ARCHT	. NO.:		S3.	1	
DATE:	4/30/202	24 7:52:	34 AM		

SCALE: 3/8" = 1'-0"


CFS HEADER SCHEDULE									
	HEADER			TRACK			JAMB		
MARK	No.	SIZE	GRADE	No.	SIZE	GRADE	No.	SIZE	GRADE
H-1	2	800\$350-54	50	2	800T125-54	50	2	8005300-97	50






SILL - JAMB DETAIL

12 /S4.0 SCALE = 3/4" = 1'-0"




JOIST STUD HEADER DETAIL

13 /S4.0 SCALE = 3/4" = 1'-0"



CORNER & DIAGONAL LAP CONNECTIONS

7 /S4.0 SCALE = 3/4" = 1'-0"




JOISTS / RAFTERS

1) FLANGES SHALL NOT BE NOTCHED OR CUT. 2) CAPACITY VERIFICATION BY DESIGN IS REQ. FOR ANY OP'GS LOCATED @ CONCENTRATED LOADS & BEARING ENDS 3) FOR UNPUNCHED MEMBERS, CONSULT JOIST MANUFACTURER


STUD PENETRATIONS DETAIL

8 /S4.0 SCALE = 3/4" = 1'-0"




EXTERIOR/BEARING STUD BRIDGING DETAIL

9 /S4.0 SCALE = 3/4" = 1'-0"




JOIST BEARING DETAIL

10 /S4.0 SCALE = 3/4" = 1'-0"



JOIST BRIDGING DETAIL


11 /S4.0 SCALE = 3/4" = 1'-0"



1) STUD TO SET TIGHT IN TRACK 2) SIM. DETAIL FOR TOP TRACK


STUD TO TRACK

1 /S4.0 SCALE = 3/4" = 1'-0"




INTERIOR SPAZZER BRACING

2 /S4.0 SCALE = 3/4" = 1'-0"




BASE TRACK TO CONCRETE

3 /S4.0 SCALE = 3/4" = 1'-0"




BOTTOM & TOP TRACK SPLICE

4 /S4.0 SCALE = 3/4" = 1'-0"



INTERIOR OPENING HEADER

5 /S4.0 SCALE = 3/4" = 1'-0"



STUD TO STUD CONNECTION

6 /S4.0 SCALE = 3/4" = 1'-0"

UCTION BUILD.

MASSMAN CORPORATE INC TRUCT. w w w SALES: DRAWN BY: Author SHEET: SMET NO.: S4.0 ARCHT. NO.:

DATE: 4/30/2024 7:52:34 AM

SCALE: 3/4" = 1'-0"